

ENVILIV ADVANCED SL TEAM



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Maraya Aubergine
OKVIR	Advanced SL-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Liv Contact SLR Aero, 31.8mm, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
OPORA KRMILA	Giant Contact SLR Aero, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
OPORA SEDEŽA	Giant Vector SLR, full-composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SEDEŽ	CADEX Amp
POGON	
PRESTAVNE ROČICE	SRAM RED AXS
PREDNJI MENJALNIK	SRAM RED AXS
ZADNJI MENJALNIK	SRAM RED AXS
ZAVORE	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
ZAVORNE ROČICE	SRAM RED AXS
VERIŽNIK	SRAM RED, 12-speed, 10x33
VERIGA	SRAM RED
GONILKE Z VERIŽNIKI	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

OBROČNIKI	
OBROČI	CADEX Ultra 50 WheelSystem, [F] 50mm, [R] 50mm
PESTA	[F] CADEX R3 Aero Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C40 Aero Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon Spoke
PLAŠČI	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODATKI	computer mount, two bottle cages, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	440	470	500	530	560
Kot sedežne cevi	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Višina glave okvirja (mm)	105	120	135	155	175
Krmilni kot	70,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	49	49	49	49	49
Trail (mm)	72,7	66,3	59,9	56,8	56,8
Medosna razdalja (mm)	970	973	977	984	996
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	67
Oddaljenost zgornje cevi od gonilne osi (mm)	499	517	532	553	569
Doseg (mm)	364	370	377	382	386
Višina zgornje cevi (mm)	706,1	731,8	761,1	787,4	815,3
Širina krmila (mm)	360	360	380	400	420
Dolžina opore krmila (mm)	80	80	90	100	110
Dolžina gonilke (mm)	165	165	170	170	172,5
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.