



## SPECS

RAMME	
FARGE	Neo Mint
RAMME	ALUXX SL-grade aluminum 130mm Flexpoint suspension
GAFFEL	CREST TR Elite Lite, FLOTUNE damper, wheel size 24", T140mm
DEMPER	CREST FLOTRAC Lite, 165x45, Trunnion Mount
KOMPONENTER	
STYRE	Giant Contact TR Riser, 20mm rise, AL6061 GA 680mm
GRIPS	Giant small-hand grip
STYRSTEM	Giant Contact, 8 Degrees, 40mm Length
SETEPINNE	Contact Switch AT Lite, T100mm
SADEL	Selle Royal VIVO JR
PEDALER	Giant Pinner Lite Pedal
DRIVVERK	
GIRHENDLER	Microshift Advent X Trail Trigger Shifter   SL-M9505-R (with nanowire)
BAKGIR	Microshift Advent X RD-M6205AM
BREMSER	Tektro F[180 rotor] R[160 rotor]
BREMSEHENDLER	Tektro HD-J285
KASSETT	Microshift Advent X G-Series 10-speed Cassette 11-48T CS-G104 11-48T
KJEDE	KMC X10 with missing link
KRANK	ProWheel CHARM-30T 30T, 140mm
BOTTOM BRACKET	Press-fit

HJUL	
FELG	TRA wheelsystem, DBL (Dynamic balance Lacing), wheel size 24"
NAV	[F] Alloy, 6 Bolt [R] Alloy, 72T Pawl Driver, 6 Bolt
EIKE	Sapim Laser
DEKK	Maxxis M301P Minion DHF 24x2.4 60 TPI Folding (Front) Maxxis M327P Minion DHR II 24x2.3 60 TPI Folding (Rear)
EXTRAS	Giant 1x Chain Guide

## GEOMETRI

RAMME	One Size
Seat Tube Length (mm)	320
Seat Tube Angle	77,0°
Top Tube Length (mm)	500
Head Tube Length (mm)	105
Head Tube Angle	64,5°
Fork Rake (mm)	30
Trail (mm)	119,2
Wheelbase (mm)	1054,1
Chain Stay Length (mm)	390
Bottom Bracket Drop (mm)	
Stack (mm)	534,6
Reach (mm)	376,6
Stand Over Height (mm)	641
Handlebar Width (mm)	680
Stem Length (mm)	40
Crank Length (mm)	140
Wheel Size	24"

Alle spesifikasjonene kan endres uten varsel.