



SPECS

FRAME	
COLORS	Neo Mint
FRAME	ALUXX SL-grade aluminum 130mm Flexpoint suspension
FORK	CREST TR Elite Lite, FLOTUNE damper, wheel size 24", T140mm
SHOCK	CREST FLOTRAC Lite, 165x45, Trunnion Mount
COMPONENTS	
HANDLEBAR	Giant Contact TR Riser, 20mm rise, AL6061 GA 680mm
GRIPS	Giant small-hand grip
STEM	Giant Contact, 8 Degrees, 40mm Length
SEATPOST	Contact Switch AT Lite, T100mm
SADDLE	Selle Royal VIVO JR
PEDALS	Giant Pinner Lite Pedal
DRIVETRAIN	
SHIFTERS	Microshift Advent X Trail Trigger Shifter SL-M9505-R (with nanowire)
REAR DERAILLEUR	Microshift Advent X RD-M6205AM
BRAKES	Tektro F[180 rotor] R[160 rotor]
BRAKE LEVERS	Tektro HD-J285
CASSETTE	Microshift Advent X G-Series 10-speed Cassette 11-48T CS-G104 11-48T
CHAIN	KMC X10 with missing link
CRANKSET	ProWheel CHARM-30T 30T, 140mm
BOTTOM BRACKET	Press-fit

WHEELS	
RIMS	TRA wheelsystem, DBL (Dynamic balance Lacing), wheel size 24"
HUBS	[F] Alloy, 6 Bolt [R] Alloy, 72T Pawl Driver, 6 Bolt
SPOKES	Sapim Laser
TIRES	Maxxis M301P Minion DHF 24x2.4 60 TPI Folding (Front) Maxxis M327P Minion DHR II 24x2.3 60 TPI Folding (Rear)
EXTRAS	Giant 1x Chain Guide

GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	320
Seat Tube Angle	77.0°
Top Tube Length (mm)	500
Head Tube Length (mm)	105
Head Tube Angle	64.5°
Fork Rake (mm)	30
Trail (mm)	119.2
Wheelbase (mm)	1054.1
Chain Stay Length (mm)	390
Bottom Bracket Drop (mm)	
Stack (mm)	534.6
Reach (mm)	376.6
Stand Over Height (mm)	641
Handlebar Width (mm)	680
Stem Length (mm)	40
Crank Length (mm)	140
Wheel Size	24"

All specifications listed are subject to change without notice.