



SPECS

| FRAME           |                                                                        |
|-----------------|------------------------------------------------------------------------|
| COLORS          | Radiant Pink                                                           |
| FRAME           | ALUXX SL-grade aluminum 135mm Flexpoint suspension Rear 26" Wheel only |
| FORK            | CREST SL, FLOTUNE damper, Lite tuning, wheel size 27.5", T140mm        |
| SHOCK           | CREST FLOTRAC Lite, 165x45, Trunnion Mount                             |
| COMPONENTS      |                                                                        |
| HANDLEBAR       | Giant Contact TR Riser, 20mm rise, AL6061 740mm                        |
| GRIPS           | Giant small-hand grip                                                  |
| STEM            | Giant Contact, 8 Degrees, 40mm Length                                  |
| SEATPOST        | Contact Switch AT Lite, T100mm                                         |
| SADDLE          | Giant Romero                                                           |
| PEDALS          | Giant Pinner Lite Pedal                                                |
| DRIVETRAIN      |                                                                        |
| SHIFTERS        | Microshift Advent X Trail Trigger Shifter   SL-M9505-R (with nanowire) |
| REAR DERAILLEUR | Microshift Advent X RD-M6205AM                                         |
| BRAKES          | Tektro F[180 rotor] R[160 rotor]                                       |
| BRAKE LEVERS    | Tektro HD-J285                                                         |
| CASSETTE        | Microshift Advent X G-Series 10-speed Cassette 11-48T CS-G104 11-48T   |
| CHAIN           | KMC X10 with missing link                                              |
| CRANKSET        | ProWheel CHARM-30T 30T, 155mm                                          |
| BOTTOM BRACKET  | Press-fit                                                              |

| WHEELS |                                                                                                                 |
|--------|-----------------------------------------------------------------------------------------------------------------|
| RIMS   | TRA wheelsystem, DBL (Dynamic balance Lacing), wheel size [F] 27.5" [R] 26"                                     |
| HUBS   | [F] Alloy, 6 Bolt [R] Alloy, 72T Pawl Driver, 6 Bolt                                                            |
| SPOKES | Sapim Laser                                                                                                     |
| TIRES  | Maxxis M301P Minion DHF 27.5x2.5 60 TPI Folding (Front) Maxxis M327P Minion DHR II 26x2.4 60 TPI Folding (Rear) |
| EXTRAS | Giant 1x Chain Guide                                                                                            |

GEOMETRY

| FRAME                    | One Size        |
|--------------------------|-----------------|
| Seat Tube Length (mm)    | 350             |
| Seat Tube Angle          | 77,0°           |
| Top Tube Length (mm)     | 545             |
| Head Tube Length (mm)    | 105             |
| Head Tube Angle          | 64,5°           |
| Fork Rake (mm)           | 41              |
| Trail (mm)               | 126,5           |
| Wheelbase (mm)           | 1147,5          |
| Chain Stay Length (mm)   | 425             |
| Bottom Bracket Drop (mm) | 10              |
| Stack (mm)               | 584,5           |
| Reach (mm)               | 410,1           |
| Stand Over Height (mm)   | 676             |
| Handlebar Width (mm)     | 740             |
| Stem Length (mm)         | 40              |
| Crank Length (mm)        | 155             |
| Wheel Size               | F 27.5" / R 26" |

All specifications listed are subject to change without notice.