



SPECIFIKACIJE

OKVIR	
BARVE	Radiant Pink
OKVIR	ALUXX SL-grade aluminum 135mm Flexpoint suspension Rear 26" Wheel only
VILICE	CREST SL, FLOTUNE damper, Lite tuning, wheel size 27.5", T1140mm
AMORTIZER	CREST FLOTRAC Lite, 165x45, Trunnion Mount
KOMPONENTE	
KRMILO	Giant Contact TR Riser, 20mm rise, AL6061 740mm
GRIPS	Giant small-hand grip
OPORA KRMILA	Giant Contact, 8 Degrees, 40mm Length
OPORA SEDEŽA	Contact Switch AT Lite, T100mm
SEDEŽ	Giant Romero
PEDALA	Giant Pinner Lite Pedal
POGON	
PRESTAVNE ROČICE	Microshift Advent X Trail Trigger Shifter SL-M9505-R (with nanowire)
ZADNJI MENJALNIK	Microshift Advent X RD-M6205AM
ZAVORE	Tektro F[180 rotor] R[160 rotor]
ZAVORNE ROČICE	Tektro HD-J285
VERIŽNIK	Microshift Advent X G-Series 10-speed Cassette 11-48T CS-G104 11-48T
VERIGA	KMC X10 with missing link
GONILKE Z VERIŽNIKI	ProWheel CHARM-30T 30T, 155mm
BOTTOM BRACKET	Press-fit

OBROČNIKI	
OBROČI	TRA wheelsystem, DBL (Dynamic balance Lacing), wheel size [F] 27.5" [R] 26"
PESTA	[F] Alloy, 6 Bolt [R] Alloy, 72T Pawl Driver, 6 Bolt
NAPERE	Sapim Laser
PLAŠČI	Maxxis M301P Minion DHF 27.5x2.5 60 TPI Folding (Front) Maxxis M327P Minion DHR II 26x2.4 60 TPI Folding (Rear)
DODATKI	Giant 1x Chain Guide

GEOMETRIJA

OKVIR	One Size
Dolžina sedežne cevi (mm)	350
Kot sedežne cevi	77,0°
Top Tube Length (mm)	545
Višina glave okvirja (mm)	105
Krmilni kot	64,5°
Zamik vpetja osi (mm)	41
Trail (mm)	126,5
Medosna razdalja (mm)	1147,5
Dolžina cevi ob verigi (mm)	425
Bottom Bracket Drop (mm)	10
Oddaljenost zgornje cevi od gonilne osi (mm)	584,5
Doseg (mm)	410,1
Višina zgornje cevi (mm)	676
Širina krmila (mm)	740
Dolžina opore krmila (mm)	40
Dolžina gonilke (mm)	155
Velikost obročnikov	F 27.5" / R 26"

Vse navedene specifikacije se lahko spremenijo brez obvestila.