



SPECS

FRAME	
COLORS	Radiant Pink
FRAME	ALUXX SL-grade aluminum 135mm Flexpoint suspension Rear 26" Wheel only
FORK	CREST SL, FLOTUNE damper, Lite tuning, wheel size 27.5", T140mm
SHOCK	CREST FLOTRAC Lite, 165x45, Trunnion Mount
COMPONENTS	
HANDLEBAR	Giant Contact TR Riser, 20mm rise, AL6061 740mm
GRIPS	Giant small-hand grip
STEM	Giant Contact, 8 Degrees, 40mm Length
SEATPOST	Contact Switch AT Lite, T100mm
SADDLE	Giant Romero
PEDALS	Giant Pinner Lite Pedal
DRIVETRAIN	
SHIFTERS	Microshift Advent X Trail Trigger Shifter SL-M9505-R (with nanowire)
REAR DERAILLEUR	Microshift Advent X RD-M6205AM
BRAKES	Tektro F[180 rotor] R[160 rotor]
BRAKE LEVERS	Tektro HD-J285
CASSETTE	Microshift Advent X G-Series 10-speed Cassette 11-48T CS-G104 11-48T
CHAIN	KMC X10 with missing link
CRANKSET	ProWheel CHARM-30T 30T, 155mm
BOTTOM BRACKET	Press-fit

WHEELS	
RIMS	TRA wheelsystem, DBL (Dynamic balance Lacing), wheel size [F] 27.5" [R] 26"
HUBS	[F] Alloy, 6 Bolt [R] Alloy, 72T Pawl Driver, 6 Bolt
SPOKES	Sapim Laser
TIRES	Maxxis M301P Minion DHF 27.5x2.5 60 TPI Folding (Front) Maxxis M327P Minion DHR II 26x2.4 60 TPI Folding (Rear)
EXTRAS	Giant 1x Chain Guide

GEOMETRY

FRAME	One Size
Seat Tube Length (mm)	350
Seat Tube Angle	77.0°
Top Tube Length (mm)	545
Head Tube Length (mm)	105
Head Tube Angle	64.5°
Fork Rake (mm)	41
Trail (mm)	126.5
Wheelbase (mm)	1147.5
Chain Stay Length (mm)	425
Bottom Bracket Drop (mm)	10
Stack (mm)	584.5
Reach (mm)	410.1
Stand Over Height (mm)	676
Handlebar Width (mm)	740
Stem Length (mm)	40
Crank Length (mm)	155
Wheel Size	F 27.5" / R 26"

All specifications listed are subject to change without notice.