

FLOURISH 3



SPECS

FRAME	
SIZES	XS, S, M
COLORS	Gunmetal Black
FRAME	ALUXX-Grade Aluminum
FORK	high-tensile steel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	alloy, low rise, 25.4mm XS:60cm, S:60cm, M:60cm
GRIPS	Liv Comfort
STEM	MTS-291, 25.4mm XS:85mm, S:85mm, M:105mm
SEATPOST	alloy, 30.9mm XS:400mm, S:400mm, M:400mm,
SADDLE	Liv Comfort
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano SL-TX50, 1x7
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Tourney
BRAKES	alloy, direct pull
BRAKE LEVERS	alloy comfort
CASSETTE	Shimano MF-TZ500, 14x28
CHAIN	KMC Z7
CRANKSET	alloy, 44t XS:170mm, S:170mm, M:175mm
BOTTOM BRACKET	sealed cartridge

WHEELS	
RIMS	Giant double-wall aluminum
HUBS	Shimano, alloy, 36h
SPOKES	stainless
TIRES	Kenda K-192, 700x38c
EXTRAS	40mm max tire size, fenders, kickstand

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	355,5	406	457
Seat Tube Angle	73,5°	73,0°	73,0°
Top Tube Length (mm)	545	565	585
Head Tube Length (mm)	130	150	190
Head Tube Angle	69,0°	69,5°	69,5°
Fork Rake (mm)	45	45	45
Trail (mm)	87,1	83,8	83,8
Wheelbase (mm)	1067	1078	1100
Chain Stay Length (mm)	455	455	455
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	586	607	644
Reach (mm)	371	379	388
Stand Over Height (mm)	419	421	432
Handlebar Width (mm)	600	600	600
Stem Length (mm)	85	85	105
Crank Length (mm)	170	170	175
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.