

FLOURISH DISC 3



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	White, Muscat Blanc
FRAME	ALUXX-Grade Aluminum, disc brake
FORK	High-tensile steel, disc brake
SHOCK	N/A
COMPONENTS	
HANDLEBAR	alloy, 26mm rise, 25.4mm XS: 59cm, S: 59cm, M: 61cm, L: 61cm
GRIPS	Liv Sport Grip, black
STEM	alloy, 25.4mm XS: 150mm, S: 150mm, M: 180mm, L: 180mm
SEATPOST	alloy, 27.2mm XS: 300mm, S: 300mm, M: 300mm, L: 350mm
SADDLE	Selle Royal Essenza+, brown
PEDALS	platform
DRIVETRAIN	
SHIFTERS	microSHIFT Acolyte, 1x8
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	microSHIFT Acolyte
BRAKES	Tektro TKB 172 [F], MD 510 [R] mechanical, rotors [F]160mm, [R]160mm
BRAKE LEVERS	alloy comfort
CASSETTE	microSHIFT, 12x42
CHAIN	KMC Z8.1
CRANKSET	ProWheel Pioneer, 38t XS: 170mm, S: 170mm, M: 175mm, L: 175mm
BOTTOM BRACKET	sealed cartridge

WHEELS	
RIMS	Giant double-wall aluminum
HUBS	alloy, 28h
SPOKES	stainless
TIRES	Kenda K-192, 700x40c
EXTRAS	42mm, or 40c max tire size, fenders, kickstand, chain cover, hem weight

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	355	430	495	515
Seat Tube Angle	73,0°	72,5°	72,0°	72,0°
Top Tube Length (mm)	540	565	585	620
Head Tube Length (mm)	160	180	200	220
Head Tube Angle	68,0°	69,0°	70,0°	70,0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	97,6	90,4	83,3	83,3
Wheelbase (mm)	1083,2	1092,5	1095,7	1131,4
Chain Stay Length (mm)	460	460	460	460
Bottom Bracket Drop (mm)	65	65	65	65
Stack (mm)	611,9	635,2	658,7	677,5
Reach (mm)	352,9	364,7	371	399,9
Stand Over Height (mm)	453	440,3	450,2	423,8
Handlebar Width (mm)	590	590	610	610
Stem Length (mm)	150	150	180	180
Crank Length (mm)	170	170	175	175
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.