

FLOURISH DISC 3



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	White, Muscat Blanc
RAMME	ALUXX-Grade Aluminum, disc brake
GAFFEL	High-tensile steel, disc brake
DEMPER	N/A
KOMPONENTER	
STYRE	alloy, 26mm rise, 25.4mm XS: 59cm, S: 59cm, M: 61cm, L: 61cm
GRIPS	Liv Sport Grip, black
STYRSTEM	alloy, 25.4mm XS: 150mm, S: 150mm, M: 180mm, L: 180mm
SETEPINNE	alloy, 27.2mm XS: 300mm, S: 300mm, M: 300mm, L: 350mm
SADEL	Selle Royal Essenza+, brown
PEDALER	platform
DRIVVERK	
GIRHENDLER	microSHIFT Acolyte, 1x8
FRONTGIR	N/A
BAKGIR	microSHIFT Acolyte
BREMSE	Tektro TKB 172 [F], MD 510 [R] mechanical, rotors [F]160mm, [R]160mm
BREMSEHENDLER	alloy comfort
KASSETT	microSHIFT, 12x42
KJEDE	KMC Z8.1
KRANK	ProWheel Pioneer, 38t XS: 170mm, S: 170mm, M: 175mm, L: 175mm
BOTTOM BRACKET	sealed cartridge

HJUL	
FELG	Giant double-wall aluminum
NAV	alloy, 28h
EIKE	stainless
DEKK	Kenda K-192, 700x40c
EXTRAS	42mm, or 40c max tire size, fenders, kickstand, chain cover, hem weight

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	355	430	495	515
Seat Tube Angle	73,0°	72,5°	72,0°	72,0°
Top Tube Length (mm)	540	565	585	620
Head Tube Length (mm)	160	180	200	220
Head Tube Angle	68,0°	69,0°	70,0°	70,0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	97,6	90,4	83,3	83,3
Wheelbase (mm)	1083,2	1092,5	1095,7	1131,4
Chain Stay Length (mm)	460	460	460	460
Bottom Bracket Drop (mm)	65	65	65	65
Stack (mm)	611,9	635,2	658,7	677,5
Reach (mm)	352,9	364,7	371	399,9
Stand Over Height (mm)	453	440,3	450,2	423,8
Handlebar Width (mm)	590	590	610	610
Stem Length (mm)	150	150	180	180
Crank Length (mm)	170	170	175	175
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.