

FLOURISH E+ 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Core2 55Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full colour LCD display
BATTERY	Giant EnergyPak 500Wh
CHARGER	Giant EnergyPak 4A smart charger
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
FRAME	
SIZES	XS, S, M
COLOURS	Midnight Moon, Golden Shimmer
FRAME	ALUXX-grade aluminium, Integrated battery design, low step-through
FORK	SR Suntour MOBIE A32 27.5" Coil 63mm travel, QR
COMPONENTS	
HANDLEBAR	Alloy Riser 31.8mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
STEM	Alloy adjustable, XS:70mm, S:70mm, M:90mm
SEATPOST	Suspension, 30.9mm, XS: 40mm travel / 30.9 x 300mm, S: 40mm travel / 30.9 x 300mm, M: 40mm travel / 30.9 x 300mm
SADDLE	Selle Royal Lift
PEDALS	Anti-slip platform
DRIVETRAIN	
SHIFTERS	Shimano Altus, 1x8
REAR DERAILLEUR	Shimano Acera, 8-speed
BRAKES	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
BRAKE LEVERS	Tektro HD-M281, hydraulic disc
CASSETTE	Shimano HG400, 8-speed, 11-44T
CHAIN	KMC E8 Sport
CRANKSET	Forged Alloy, 38T, XS:160mm, S:165mm, M:165mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant eX25, Tubeless Ready, Aluminium
HUBS	Shimano HB-QC300, QR, Disc 32H [F] Shimano FH-QC300-HM, Disc 32H [R]
SPOKES	Stainless steel
TYRES	Kenda Kwick Seven 5, 27.5X2.2 Wire 60TPI Brown w/ reflex stripe
EXTRAS	KSA18 direct mount kickstand, compatible with [F] & [R] Aegis tyre checker, EnergyPak Plus 200
LIMITS	
NSW CERTIFICATION	ULL-104280-EA
ACCESSORIES	
LIGHTING	Giant Recon HL50, 50 lux [F] Fender mounted tail light [R]
LOCK	ABUS Xplus battery lock
CARRIER	Front basket
FENDER/CHAINGUARD	Aluminium fenders

Price: \$4,799.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	380	450	520
Seat Tube Angle	75.0°	73.0°	71.0°
Top Tube Length (mm)	570	590	610
Head Tube Length (mm)	170	170	170
Head Tube Angle	69.0°	69.0°	69.0°
Fork Rake (mm)	44	44	44
Trail (mm)	91	91	91
Wheelbase (mm)	1127	1127	1127
Chain Stay Length (mm)	650	650	650
Bottom Bracket Drop (mm)	55	55	55
Stack (mm)	631	631	631
Reach (mm)	380	380	380
Stand Over Height (mm)	401	419	419
Stem Length (mm)	70	90	110
Crank Length (mm)	160	165	165
Wheel Size	27.5	27.5	27.5

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.