



SPECS

FRAME	
SIZES	XS, S, M
COLORS	Eclipse, Desert Sage
FRAME	ALUXX-Grade Aluminum
FORK	CR7V T40, 40mm
SHOCK	N/A
COMPONENTS	
HANDLEBAR	alloy, low rise, 25.4mm XS:60cm, S:60cm, M:60cm
GRIPS	Liv Comfort
STEM	MQ-576 adjustable, 25.4mm XS:85mm, S:85mm, M:105mm
SEATPOST	alloy, suspension, 30.9mm XS:350mm, S:350mm, M:350mm
SADDLE	Liv Comfort
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano EF500, 3x8
FRONT DERAILLEUR	Shimano Tourney TY710
REAR DERAILLEUR	Shimano Altus M310
BRAKES	alloy, direct pull
BRAKE LEVERS	alloy
CASSETTE	Shimano Altus HG31, 11x34
CHAIN	KMC Z8.3
CRANKSET	forged alloy, 28/38/48 XS:170mm, S:170mm, M:175mm
BOTTOM BRACKET	sealed cartridge

WHEELS	
RIMS	Giant double-wall aluminum
HUBS	Shimano, alloy, 36h
SPOKES	stainless
TIRES	Kenda K-192, 700x38c
EXTRAS	40mm max tire size, rear rack, fenders, kickstand

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	355,5	406	457
Seat Tube Angle	73,5°	73,0°	73,0°
Top Tube Length (mm)	545	565	585
Head Tube Length (mm)	130	150	190
Head Tube Angle	69,0°	69,5°	69,5°
Fork Rake (mm)	45	45	45
Trail (mm)	87,1	83,8	83,8
Wheelbase (mm)	1067	1078	1100
Chain Stay Length (mm)	455	455	455
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	586	607	644
Reach (mm)	371	379	388
Stand Over Height (mm)	419	421	432
Handlebar Width (mm)	600	600	600
Stem Length (mm)	85	85	105
Crank Length (mm)	170	170	175
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.