

INTRIGUE 29 1



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | S, M, L |
| COLOURS | Kelp Forest |
| FRAME | ALUXX SL-grade aluminum front and rear triangles, 125mm Maestro Suspension, flip chip - Maestro |
| FORK | Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset |
| SHOCK | Fox Float Performance 185x50, custom tuned for Liv |
| COMPONENTS | |
| HANDLEBAR | Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm |
| GRIPS | Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm |
| STEM | Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm |
| SEATPOST | Giant Contact Switch dropper, adjustable, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm |
| SADDLE | Liv Sylvia |
| PEDALS | platform |
| DRIVETRAIN | |
| SHIFTERS | Shimano Deore, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | Shimano Deore, Shadow + |
| BRAKES | Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm |
| BRAKE LEVERS | Shimano BL-MT401 |
| CASSETTE | Shimano Deore M6100, 10x51 |
| CHAIN | KMC X12 |
| CRANKSET | Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm |
| BOTTOM BRACKET | Praxis, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width |
| HUBS | [F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing |
| SPOKES | Sapim |
| TIRES | [F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| EXTRAS | tubeless prepared, max tire size 2.5", max chainring size 32t |

Suggested Retail Price (CDN): \$3,499.00

FRAME GEOMETRY

| FRAME | S | M | L |
|--------------------------------|---------------|---------------|---------------|
| | LOW HIGH | LOW HIGH | LOW HIGH |
| Seat Tube Length (mm) | 425 | 435 | 460 |
| Seat Post Insertion Depth (mm) | 295 | 305 | 330 |
| Seat Tube Angle | 77.0° 77.8° | 77.0° 77.8° | 77.0° 77.8° |
| Top Tube Length (mm) | 558 557 | 574 573 | 599 597 |
| Head Tube Length (mm) | 105 | 110 | 125 |
| Head Tube Angle | 65.8° 66.5° | 65.8° 66.5° | 65.8° 66.5° |
| Fork Rake (mm) | 44 | 44 | 44 |
| Trail (mm) | 122 117 | 122 117 | 122 117 |
| Wheelbase (mm) | 1160 1160 | 1177 1176 | 1205 1204 |
| Chain Stay Length (mm) | 438 435 | 438 435 | 438 435 |
| Bottom Bracket Drop (mm) | 40 30 | 40 30 | 40 30 |
| Stack (mm) | 620 614 | 625 618 | 639 632 |
| Reach (mm) | 415 424 | 430 438 | 451 460 |
| Stand Over Height (mm) | 742 751 | 732 741 | 751 759 |
| Handlebar Width (mm) | 760 | 760 | 780 |
| Stem Length (mm) | 50 | 50 | 50 |
| Crank Length (mm) | 170 | 170 | 175 |
| Wheel Size | [F] 29" [R] | [F] 29" [R] | [F] 29" [R] |

All prices and specifications are subject to change without notice.