

# INTRIGUE 29 1



## SPECS

FRAME	
<b>SIZES</b>	S, M, L
<b>COLORS</b>	Smoke Metal / Dark Gray
<b>FRAME</b>	ALUXX SL-Grade Aluminum front and rear triangles, 125mm Maestro Suspension, flip chip
<b>FORK</b>	Fox 34 Float Performance, 140mm, GRIP damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
<b>SHOCK</b>	Fox Float DPS Performance, 185/50, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, alloy, 35mm S:760mm, M:760mm, L:780mm
<b>GRIPS</b>	Liv Supera, single lock ring
<b>STEM</b>	Giant Contact SL, 35mm S:50mm, M:50mm, L:50mm
<b>SEATPOST</b>	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 499mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano SLX M7100, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano SLX M7100
<b>BRAKES</b>	Tektro HDM475
<b>BRAKE LEVERS</b>	Tektro HDM475
<b>CASSETTE</b>	Shimano SLX M7100, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Shimano M511, 30t S:170mm, M:170mm, L:170mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
<b>HUBS</b>	[F] alloy 15x110, sealed bearing [R] alloy 12x148, sealed bearing
<b>SPOKES</b>	Sapim
<b>TIRES</b>	[F] Maxxis Minion DHF 29x2.5WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, EXO, TR, tubeless
<b>EXTRAS</b>	tubeless prepared, max tire size 2.5", max chainring size 32t

**Recommended Retail Price: \$3,600.00**

## GEOMETRY

FRAME	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (inch)	16.7	17.1	17.1	18.1	18.1	18.1
Seat Tube Angle	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°
Top Tube Length (inch)	22   21.9	22.6   22.6	23.6   23.5	23.6   23.5	23.6   23.5	23.6   23.5
Head Tube Length (inch)	4.1	4.3	4.9	4.9	4.9	4.9
Head Tube Angle	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°
Fork Rake (inch)	1.7	1.7	1.7	1.7	1.7	1.7
Trail (inch)	4.8   4.6	4.8   4.6	4.8   4.6	4.8   4.6	4.8   4.6	4.8   4.6
Wheelbase (inch)	45.7   45.7	46.3   46.3	47.4   47.4	47.4   47.4	47.4   47.4	47.4   47.4
Chain Stay Length (inch)	17.2   17.1	17.2   17.1	17.2   17.1	17.2   17.1	17.2   17.1	17.2   17.1
Bottom Bracket Drop (inch)	1.6   1.2	1.6   1.2	1.6   1.2	1.6   1.2	1.6   1.2	1.6   1.2
Stack (inch)	24.4   24.2	24.6   24.3	25.2   24.9	25.2   24.9	25.2   24.9	25.2   24.9
Reach (inch)	16.3   16.7	16.9   17.2	17.8   18.1	17.8   18.1	17.8   18.1	17.8   18.1
Stand Over Height (inch)	28.8   29.1	29   29.4	29.8   30.1	29.8   30.1	29.8   30.1	29.8   30.1
Handlebar Width (inch)	29.9	29.9	30.7	30.7	30.7	30.7
Stem Length (inch)	2	2	2	2	2	2
Crank Length (inch)	6.7	6.7	6.9	6.9	6.9	6.9
Wheel Size	29"	29"	29"	29"	29"	29"

*\*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*