

# INTRIGUE 29 1



## ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L
COLORES	Brush Aluminum/Black Diamond
CUADRO	ALUXX SL-Grade Aluminum front and rear triangles, 125mm Maestro Suspension, flip chip
TIJERA	Fox 36 Float Performance, 140mm, GRIP damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
AMORTIGUADOR	Fox Float DPS Performance, 185/50, custom tuned for Liv
COMPONENTES	
MANUBRIO	Giant Contact SL TR35, alloy, 35mm S:760mm, M:760mm, L:780mm
GRIPS	Liv Tactal single lock-on XS/S: 120mm, M/L: 130mm
POTENCIA	Giant Contact SL, 35mm S:50mm, M:50mm, L:50mm
POSTE DE ASIENTO	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel /
ASIENTO	Liv Sylvia
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano SLX M7100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano SLX M7100, Shadow+
FRENOS	Tektro M750, hydraulic, Tektro rotors [F]180mm, [R]180mm
PALANCAS DE FRENOS	Tektro HDM-750
CASSETTE	Shimano SLX M7100, 10x51
CADENA	KMC X-12
MULTIPLICACIÓN	Shimano SLX M7100, 30t S:170mm, M:170mm, L:170mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
MAZAS	[F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing
RAYOS	Sapim
NEUMÁTICOS	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

**Precio: \$82,900.00**

## GEOMETRÍA

CUADRO	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	425	435	460			
Ángulo de la Base del Poste de Asiento	77.0°	77.8°	77.0°	77.8°	77.0°	77.8°
Longitud del Tubo Superior (mm)	558	557	574	573	599	597
Longitud del Telescopio (mm)	105		110		125	
Ángulo del Telescopio	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Rake (mm)	44		44		44	
Trail (mm)	122	117	122	117	122	117
Distancia entre Ejes (mm)	1160	1160	1177	1176	1205	1204
Longitud de Vaina Inferior (mm)	438	435	438	435	438	435
Caída del Eje de Centro (mm)	40	30	40	30	40	30
Stack (mm)	620	614	625	618	639	632
Reach (mm)	415	424	430	438	451	460
Altura del Tubo Superior al Suelo (mm)	731	740	737	746	756	765
Ancho del Manubrio (mm)	760		760		780	
Longitud de la Potencia (mm)	50		50		50	
Longitud de la Biela (mm)	170		170		175	
Tamaño de las Ruedas	29"		29"		29"	

*Todas las especificaciones están sujetas a cambios sin previo aviso.*