INTRIGUE 29 1



SPECS

FRAME	
SIZES	S, M, L
COLORS	Kelp Forest
FRAME	ALUXX SL-grade aluminum front and rear triangles, 125mm Maestro Suspension, flip chip – Maestro
FORK	Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset
SHOCK	Fox Float Performance 185x50, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
STEM	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
SEATPOST	Giant Contact Switch dropper, adjustable, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, Shadow +
BRAKES	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X12
CRANKSET	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
HUBS	[F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRY

FRAME	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	425	435	460
Seat Post Insertion Depth (mm)	295	305	330
Seat Tube Angle	77,0° | 77,8°	77,0° | 77,8°	77,0° | 77,8°
Top Tube Length (mm)	558 | 557	574 | 573	599 | 597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65,8° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Fork Rake (mm)	44	44	44
Trail (mm)	122 | 117	122 | 117	122 | 117
Wheelbase (mm)	1160 | 1160	1177 | 1176	1205 | 1204
Chain Stay Length (mm)	438 | 435	438 | 435	438 | 435
Bottom Bracket Drop (mm)	40 | 30	40 | 30	40 | 30
Stack (mm)	620 | 614	625 | 618	639 | 632
Reach (mm)	415 | 424	430 | 438	451 | 460
Stand Over Height (mm)	742 | 751	732 | 741	751 | 759
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	[F] 29" [R	[F] 29" [R	[F] 29" [R

All specifications listed are subject to change without notice.