



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L
BARVE	Smoke Metal / Dark Gray
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 125mm Maestro Suspension, flip chip
VILICE	Fox 34 Float Performance, 140mm, GRIP damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
AMORTIZER	Fox Float DPS Performance, 185/50, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 35mm S:760mm, M:760mm, L:780mm
GRIPS	Liv Supera, single lock ring
OPORA KRMILA	Giant Contact SL, 35mm S:50mm, M:50mm, L:50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 499mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano SLX M7100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX M7100
ZAVORE	Shimano BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano MT501
VERIŽNIK	Shimano SLX M7100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Shimano M511, 30t S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
PESTA	[F] alloy 15x110, sealed bearing [R] alloy 12x148, sealed bearing
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, EXO, TR, tubeless
DODATKI	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Dolžina sedežne cevi (mm)	425	435	460
Kot sedežne cevi	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°
Top Tube Length (mm)	558 557	574 573	599 597
Višina glave okvirja (mm)	105	110	125
Krmilni kot	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Zamik vpetja osi (mm)	44	44	44
Trail (mm)	122 117	122 117	122 117
Medosna razdalja (mm)	1160 1160	1177 1176	1205 1204
Dolžina cevi ob verigi (mm)	438 435	438 435	438 435
Bottom Bracket Drop (mm)	40 30	40 30	40 30
Oddaljenost zgornje cevi od gonilne osi (mm)	620 614	625 618	639 632
Doseg (mm)	415 424	430 438	451 460
Višina zgornje cevi (mm)	731 740	737 746	756 765
Širina krmila (mm)	760	760	780
Dolžina opore krmila (mm)	50	50	50
Dolžina gonilke (mm)	170	170	175
Velikost obročnikov	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.