



SPECIFIKACIJE

| OKVIR               |                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| VELIKOSTI           | S, M, L                                                                                                                                                   |
| BARVE               | Kelp Forest                                                                                                                                               |
| OKVIR               | ALUXX SL-grade aluminum front and rear triangles, 125mm Maestro Suspension, flip chip – Maestro                                                           |
| VILICE              | Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset                                                                       |
| AMORTIZER           | Fox Float Performance 185x50, custom tuned for Liv                                                                                                        |
| KOMPONENTE          |                                                                                                                                                           |
| KRMILO              | Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm                                                                                   |
| GRIPS               | Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm                                                                                                        |
| OPORA KRMILA        | Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm                                                                                                          |
| OPORA SEDEŽA        | Giant Contact Switch dropper, adjustable, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm |
| SEDEŽ               | Liv Sylvia                                                                                                                                                |
| PEDALA              | platform                                                                                                                                                  |
| POGON               |                                                                                                                                                           |
| PRESTAVNE ROČICE    | Shimano Deore, 1x12                                                                                                                                       |
| PREDNJI MENJALNIK   | N/A                                                                                                                                                       |
| ZADNJI MENJALNIK    | Shimano Deore, Shadow +                                                                                                                                   |
| ZAVORE              | Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm                                                                                      |
| ZAVORNE ROČICE      | Shimano BL-MT401                                                                                                                                          |
| VERIŽNIK            | Shimano Deore M6100, 10x51                                                                                                                                |
| VERIGA              | KMC X12                                                                                                                                                   |
| GONILKE Z VERIŽNIKI | Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm                                                                           |
| BOTTOM BRACKET      | Praxis, press fit                                                                                                                                         |

| OBROČNIKI |                                                                                                                                |
|-----------|--------------------------------------------------------------------------------------------------------------------------------|
| OBROČI    | Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width                                                                    |
| PESTA     | [F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing                                                             |
| NAPERE    | Sapim                                                                                                                          |
| PLAŠČI    | [F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| DODATKI   | tubeless prepared, max tire size 2.5", max chainring size 32t                                                                  |

GEOMETRIJA

| OKVIR                                        | S             | M             | L             |
|----------------------------------------------|---------------|---------------|---------------|
|                                              | LOW   HIGH    | LOW   HIGH    | LOW   HIGH    |
| Dolžina sedežne cevi (mm)                    | 425           | 435           | 460           |
| Seat Post Insertion Depth (mm)               | 295           | 305           | 330           |
| Kot sedežne cevi                             | 77,0°   77,8° | 77,0°   77,8° | 77,0°   77,8° |
| Top Tube Length (mm)                         | 558   557     | 574   573     | 599   597     |
| Višina glave okvirja (mm)                    | 105           | 110           | 125           |
| Krmilni kot                                  | 65,8°   66,5° | 65,8°   66,5° | 65,8°   66,5° |
| Zamik vpetja osi (mm)                        | 44            | 44            | 44            |
| Trail (mm)                                   | 122   117     | 122   117     | 122   117     |
| Medosna razdalja (mm)                        | 1160   1160   | 1177   1176   | 1205   1204   |
| Dolžina cevi ob verigi (mm)                  | 438   435     | 438   435     | 438   435     |
| Bottom Bracket Drop (mm)                     | 40   30       | 40   30       | 40   30       |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 620   614     | 625   618     | 639   632     |
| Doseg (mm)                                   | 415   424     | 430   438     | 451   460     |
| Višina zgornje cevi (mm)                     | 742   751     | 732   741     | 751   759     |
| Širina krmila (mm)                           | 760           | 760           | 780           |
| Dolžina opore krmila (mm)                    | 50            | 50            | 50            |
| Dolžina gonilke (mm)                         | 170           | 170           | 175           |
| Velikost obročnikov                          | [F] 29" [R]   | [F] 29" [R]   | [F] 29" [R]   |

Vse navedene specifikacije se lahko spremenijo brez obvestila.