INTRIGUE 29 1



SPECS

RAM	
STORLEKAR	S, M, L
FÄRGER	Kelp Forest
RAM	ALUXX SL-grade aluminum front and rear triangles, 125mm Maestro Suspension, flip chip – Maestro
GAFFEL	Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset
BAKDÄMPARE	Fox Float Performance 185x50, custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
GREPPAR	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
STAM	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
SADELSTOLPE	Giant Contact Switch dropper, adjustable, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SADEL	Liv Sylvia
PEDALER	platform
DRIVLINA	
VÄXLAR	Shimano Deore, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano Deore, Shadow +
BROMSAR	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
BROMSSPAKAR	Shimano BL-MT401
KASSETT	Shimano Deore M6100, 10x51
KEDJA	KMC X12
VEVPARTI	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BROMSREGLAGE	Praxis, press fit

HJUL	
FÄLGAR	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
NAV	[F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing
EKRAR	Sapim
DÄCK	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAFUNKTIONER	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRY

RAM	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH
Längd sadelrör (mm)	425	435	460
Seat Post Insertion Depth (mm)	295	305	330
Vinkel sadelrör	77,0° | 77,8°	77,0° | 77,8°	77,0° | 77,8°
Topprörets längd (mm)	558 | 557	574 | 573	599 | 597
Styrhuvud Längd (mm)	105	110	125
Vinkel styrhuvud	65,8° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Gaffelvinkel (mm)	44	44	44
Spår (mm)	122 | 117	122 | 117	122 | 117
Hjulbas (mm)	1160 | 1160	1177 | 1176	1205 | 1204
Kedjestagslängd (mm)	438 | 435	438 | 435	438 | 435
Nedre fäste Drop (mm)	40 | 30	40 | 30	40 | 30
Stack (mm)	620 | 614	625 | 618	639 | 632
Reach (mm)	415 | 424	430 | 438	451 | 460
Stå över höjden (mm)	742 | 751	732 | 741	751 | 759
Styrets bredd (mm)	760	760	780
Stamlängd (mm)	50	50	50
Vevlängd (mm)	170	170	175
Hjulstorlek	[F] 29" [R	[F] 29" [R	[F] 29" [R

All specifications listed are subject to change without notice.