



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L
BARVE	Pistachio / Rifle Green
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 125mm Maestro Suspension, flip chip
VILICE	RockShox 35 Gold RL, 140mm, Boost, 15x110, tapered, 44mm offset, custom tuned for Liv
AMORTIZER	Fox Float DPS Performance, 185/50, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 35mm S:760mm, M:760mm, L:780mm
GRIPS	Liv Supera, single lock ring
OPORA KRMILA	Giant Contact SL, 35mm S:50mm, M:50mm, L:50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 499mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM SX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM SX Eagle
ZAVORE	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore BL-MT401
VERIŽNIK	SRAM SX, 11x50
VERIGA	SRAM SX Eagle
GONILKE Z VERIŽNIKI	SRAM SX, 30t S:170mm, M:170mm, L:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
PESTA	[F] alloy 15x110, sealed bearing [R] alloy 12x148, sealed bearing
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5WT, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, EXO, TR, tubeless
DODATKI	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	425	435	460	460	460	460
Kot sedežne cevi	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,8°
Top Tube Length (mm)	558 557	574 573	599 597	599 597	599 597	599 597
Višina glave okvirja (mm)	105	110	110	110	110	110
Krmilni kot	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Zamik vpetja osi (mm)	44	44	44	44	44	44
Trail (mm)	122 117	122 117	122 117	122 117	122 117	122 117
Medosna razdalja (mm)	1160 1160	1177 1176	1205 1204	1205 1204	1205 1204	1205 1204
Dolžina cevi ob verigi (mm)	438 435	438 435	438 435	438 435	438 435	438 435
Bottom Bracket Drop (mm)	40 30	40 30	40 30	40 30	40 30	40 30
Oddaljenost zgornje cevi od gonilne osi (mm)	620 614	625 618	639 632	639 632	639 632	639 632
Doseg (mm)	415 424	430 438	451 460	451 460	451 460	451 460
Višina zgornje cevi (mm)	731 740	737 746	756 765	756 765	756 765	756 765
Širina krmila (mm)	760	760	780	780	780	780
Dolžina opore krmila (mm)	50	50	50	50	50	50
Dolžina gonilke (mm)	170	170	175	175	175	175
Velikost obročnikov	29"	29"	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.