INTRIGUE ADVANCED 29 1



SPECS

FRAME	
SIZES	S, M, L
COLOURS	Ice Age
FRAME	Advanced-grade composite front and rear triangles, 125mm Maestro Suspension, flip chip – Maestro
FORK	Fox 34 Performance, 140mm, Grip 2 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
SHOCK	Fox Float X Performance 185x50, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
STEM	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano SLX M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M7100, Shadow +
BRAKES	Shimano M6120, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX, 10x51
CHAIN	KMC X12
CRANKSET	Shimano MT512-1, 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

Suggested Retail Price (CDN): $6,099.00

FRAME GEOMETRY

FRAME	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	425	435	460
Seat Post Insertion Depth (mm)	295	305	330
Seat Tube Angle	77.0° | 77.8°	77.0° | 77.8°	77.0° | 77.8°
Top Tube Length (mm)	558 | 557	574 | 573	599 | 597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65.8° | 66.5°	65.8° | 66.5°	65.8° | 66.5°
Fork Rake (mm)	44	44	44
Trail (mm)	122 | 117	122 | 117	122 | 117
Wheelbase (mm)	1160 | 1160	1177 | 1176	1205 | 1204
Chain Stay Length (mm)	438 | 435	438 | 435	438 | 435
Bottom Bracket Drop (mm)	40 | 30	40 | 30	40 | 30
Stack (mm)	620 | 614	625 | 618	639 | 632
Reach (mm)	415 | 424	430 | 438	451 | 460
Stand Over Height (mm)	742 | 751	732 | 741	751 | 759
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	[F] 29" [R	[F] 29" [R	[F] 29" [R

All prices and specifications are subject to change without notice.