INTRIGUE ADVANCED 29 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L
BARVE	Ice Age
OKVIR	Advanced-grade composite front and rear triangles, 125mm Maestro Suspension, flip chip – Maestro
VILICE	Fox 34 Performance, 140mm, Grip 2 damper, Boost, 15x110, Kabolt, tapered, 44mm offset
AMORTIZER	Fox Float X Performance 185x50, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
OPORA KRMILA	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano SLX M7100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX M7100, Shadow +
ZAVORE	Shimano M6120, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore BL-M6100
VERIŽNIK	Shimano SLX, 10x51
VERIGA	KMC X12
GONILKE Z VERIŽNIKI	Shimano MT512-1, 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	S	M	L
	LOW | HIGH	LOW | HIGH	LOW | HIGH
Dolžina sedežne cevi (mm)	425	435	460
Seat Post Insertion Depth (mm)	295	305	330
Kot sedežne cevi	77,0° | 77,8°	77,0° | 77,8°	77,0° | 77,8°
Top Tube Length (mm)	558 | 557	574 | 573	599 | 597
Višina glave okvirja (mm)	105	110	125
Krmilni kot	65,8° | 66,5°	65,8° | 66,5°	65,8° | 66,5°
Zamik vpetja osi (mm)	44	44	44
Trail (mm)	122 | 117	122 | 117	122 | 117
Medosna razdalja (mm)	1160 | 1160	1177 | 1176	1205 | 1204
Dolžina cevi ob verigi (mm)	438 | 435	438 | 435	438 | 435
Bottom Bracket Drop (mm)	40 | 30	40 | 30	40 | 30
Oddaljenost zgornje cevi od gonilne osi (mm)	620 | 614	625 | 618	639 | 632
Doseg (mm)	415 | 424	430 | 438	451 | 460
Višina zgornje cevi (mm)	742 | 751	732 | 741	751 | 759
Širina krmila (mm)	760	760	780
Dolžina opore krmila (mm)	50	50	50
Dolžina gonilke (mm)	170	170	175
Velikost obročnikov	[F] 29" [R	[F] 29" [R	[F] 29" [R

Vse navedene specifikacije se lahko spremenijo brez obvestila.