

INTRIGUE ADVANCED 29 2



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L
VÄRIT	Terracotta
RUNKO	Advanced-grade composite front and rear triangles, 125mm Maestro Suspension, flip chip - Maestro
HAARUKKA	Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset
ISKUNVAIMENNIN	Fox Float Performance 185x50, custom tuned for Liv
KOMPONENTIT	
OHJAUSTANKO	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
GRIPIT	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
OHJAINKANNATIN	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
SATULATOLPPA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
SATULA	Liv Sylvia
POLKIMET	platform
VOIMANSIIRTO	
VAIHDEVIPU	SRAM SX Eagle, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM SX Eagle
JARRUT	Shimano BR-MT420, hydraulic, Shimano BL-MT401 rotors [F]180mm, [R]180mm
JARRUKAHVAT	Shimano BL-MT401
RATASPAKKA	SRAM SX, 11x50
KETJUT	SRAM SX Eagle
KAMPISARJA	SRAM SX, 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
NAVAT	[F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing
PINNAT	Sapim
RENKAAT	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
LISÄTIEDOT	tubeless prepared, max tire size 2.5", max chainring size 32t

Suositusuhinta: 4 559,00 €

GEOMETRIA

RUNKO	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	425	435	435	460		
Satulatolpan asennussyvyys (mm)	295	305	330			
Satulaputken kulma	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°			
Vaakaputken pituus (mm)	558 557	574 573	599 597			
Emäputken pituus (mm)	105	110	125			
Emäputken kulma	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°			
Haarukan offset (mm)	44	44	44			
Trail-mitta (mm)	122 117	122 117	122 117			
Akseliväli (mm)	1160 1160	1177 1176	1205 1204			
Takahaarukan alaputken pituus (mm)	438 435	438 435	438 435			
Keskiön pudotus (mm)	40 30	40 30	40 30			
Stack-mitta (mm)	620 614	625 618	639 632			
Reach-mitta (mm)	415 424	430 438	451 460			
Standover-mitta (mm)	742 751	732 741	751 759			
Ohjaustangon leveys (mm)	760	760	780			
Ohjainkannattimen pituus (mm)	50	50	50			
Kammen pituus (mm)	170	170	175			
Rengaskoko	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]			

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.