

INTRIGUE ADVANCED 29 2



SPECIFICATIES

FRAME	
MATEN	S, M, L
KLEUREN	Terracotta
FRAME	Advanced-grade composite front and rear triangles, 125mm Maestro Suspension, flip chip - Maestro
VOORVORK	Marzocchi Bomber Z2, 140mm, Rail damper, Boost 15x110, Kabolt, tapered, 44mm offset
DEMPER	Fox Float Performance 185x50, custom tuned for Liv
ONDERDELEN	
STUUR	Giant Contact TR35, alloy, 35mm, 20mm rise S: 760mm, M: 760mm, L: 780mm
HANDVATTEN	Liv Tactal Pro Single Lock-On S: 120mm, M/L: 130mm
STUURPEN	Giant Contact SL, 35mm S: 50mm, M: 50mm, L: 50mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 140-170mm travel / 30.9 x 499mm
ZADEL	Liv Sylvia
PEDALEN	platform
AFMONTAGE	
SHIFTERS	SRAM SX Eagle, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM SX Eagle
REMMEN	Shimano BR-MT420, hydraulic, Shimano BL-MT401 rotors [F]180mm, [R]180mm
REMHENDELS	Shimano BL-MT401
CASSETTE	SRAM SX, 11x50
AANDRIJVING	SRAM SX Eagle
CRANKSET	SRAM SX, 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant AM 29, tubeless ready, sleeve-joint, 30mm inner width
NAVEN	[F] alloy 15x110, sealed bearing, [R] alloy 12x148, sealed bearing
SPAKEN	Sapim
BANDEN	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRA'S	tubeless prepared, max tire size 2.5", max chainring size 32t

Adviesprijs: € 4.399,00

GEOMETRIE

FRAME	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis lengte (mm)	425	435	435	460	460	460
Seat Post Insertion Depth (mm)	295	305	305	330	330	330
Zitbuis hoek	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°
Frame Lengte (horizontaal) (mm)	558 557	574 573	599 597	599 597	599 597	599 597
Balhoofdbuis Lengte (mm)	105	110	110	125	125	125
Balhoofdbuis Hoek	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Vork Sprong (mm)	44	44	44	44	44	44
Naloop (mm)	122 117	122 117	122 117	122 117	122 117	122 117
Wielbasis (mm)	1160 1160	1177 1176	1205 1204	1205 1204	1205 1204	1205 1204
Liggende achtervork lengte (mm)	438 435	438 435	438 435	438 435	438 435	438 435
Bottom Bracket Drop (mm)	40 30	40 30	40 30	40 30	40 30	40 30
Stack (mm)	620 614	625 618	639 632	639 632	639 632	639 632
Reach (mm)	415 424	430 438	451 460	451 460	451 460	451 460
Stand Over Height (mm)	742 751	732 741	751 759	751 759	751 759	751 759
Stuur breedte (mm)	760	760	780	780	780	780
Stuurpen Lengte (mm)	50	50	50	50	50	50
Cranklengte (mm)	170	170	175	175	175	175
Wielmaat	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.