INTRIGUE ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	Giant RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
CLASSIFICATION	ASTM/EN Class 4 EN17406 / ISO4210-2M
DISPLAY	RideControl GO LUX, frame integrated LED display ANT+
BATTERY	EnergyPak Smart 560Wh EnergyPak Plus 280 range extender included
CHARGER	48V 4A Smart Charger X
FRAME	
SIZES	XS, S, M
COLOURS	Stardust Grey
FRAME	Advanced-grade composite, Advanced Forged Composite Upper Rocker, 150mm Maestro suspension system, 3 position flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 36 Performance, 160mm travel, 44mm offset, GRIP damper, 3 position, Kabolt-X 15x110mm thru-axle
SHOCK	Fox Float X Performance, EVOL Large Volume sleeve, 2 position lever, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, alloy, 27mm rise
GRIPS	Liv Tactal Pro Single lock-on
STEM	Giant Contact SL Trail integrated, alloy, 27mm rise, 40 mm
SEATPOST	Giant Contact Switch E, electronic travel-adjust dropper post XS: 100mm travel / 30.9 x 374mm S: 140mm travel / 30.9 x 457mm M:170mm travel / 30.9 x 514mm
SADDLE	Liv Sylvia SL HD
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, Rocker Paddle, 1x12
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	TRP EVO Expert, hydraulic, TRP 2.3mm rotors [F]220mm, [R]203mm
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM GX XS-1270 Eagle Transmission 10-52T
CHAIN	KMC eFlatHT
CRANKSET	Praxis e-HD alloy crank arms SRAM Eagle Transmission steel direct mount, 36T chain ring XS:155mm, S:155mm, M: 155mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant E-TRA Hookless Tubeless ready Alloy 29" [F] 27.5" [R] 30mm inner width
HUBS	[F] Giant E-TRA MTB Alloy Hub, 6 Bolt, 28H [R] Giant E-TRA MTB Alloy Hub, HG Drive Body 72T Helical-Bevel Ratchet Driver, 6 Bolt, 28H
SPOKES	Sapim Laser, e-bike optimised
TYRES	Maxxis Assagai 29x2.5" foldable, Tubeless, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" foldable, Tubeless, EXO+ 3C Maxx Terra [R]
EXTRAS	Tyre Pressure Management System, Torx 25 Battery Lock with built-in Torque limiter, Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
FENDER/CHAINGUARD	Co-moulded guide 32-36T adjustable
LIMITS	
COMBINED MAX LOAD LIMIT	140 kg

Price: $11,999.00

GEOMETRY

FRAME	XS	S	M
	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	380	400	425
Seat Post Insertion Depth (mm)	262.4	262.4	289.4
Seat Tube Angle	76.6° | 77.0° | 77.4°	76.6° | 77.0° | 77.4°	76.6° | 77.0° | 77.4°
Top Tube Length (mm)	552 | 550 | 548	565 | 563 | 561	598 | 596 | 594
Head Tube Length (mm)	95	105	115
Head Tube Angle	64.1° | 64.5° | 64.9°	64.1° | 64.5° | 64.9°	64.1° | 64.5° | 64.9°
Fork Rake (mm)	44	44	44
Trail (mm)	125.4 | 122.5 | 119.6	125.4 | 122.5 | 119.6	125.4 | 122.5 | 119.6
Wheelbase (mm)	1184 | 1183 | 1182	1199 | 1198 | 1197	1232 | 1231 | 1230
Chain Stay Length (mm)	443 | 443 | 443	443 | 443 | 443	443 | 443 | 443
Bottom Bracket Drop (mm)	17 | 12 | 7	17 | 12 | 7	17 | 12 | 7
Stack (mm)	620 | 618 | 615	629 | 627 | 624	638 | 636 | 633
Reach (mm)	409 | 412 | 415	420 | 423 | 426	448 | 452 | 455
Stand Over Height (mm)	722 | 727 | 732	730 | 735 | 740	730 | 735 | 740
Stem Length (mm)	40	40	40
Crank Length (mm)	155	155	155
Wheel Size	F29"/R27.5"	F29"/R27.5"	F29"/R27.5"

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.*