

INTRIGUE ADVANCED PRO 29 0



SPECS

FRAME	
SIZES	S, M, L
COLORS	Supernova
FRAME	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
FORK	Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
SHOCK	Fox Float DPX2 Factory Live Valve [185/50], custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, 780x35
STEM	Giant Contact SL 35
SEATPOST	Fox Transfer Factory dropper, Shimano remote lever, 30.9
SADDLE	Liv Sylvia SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore XT
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano XTR
BRAKES	Shimano Deore XT
BRAKE LEVERS	Shimano Deore XT
CASSETTE	Shimano Deore XT, 10x51
CHAIN	Shimano
CRANKSET	Shimano Deore XT, 30t with MRP AMg V2 carbon guide
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant TRX-1 29 WheelSystem
HUBS	Giant TRX-1 29 WheelSystem
SPOKES	Giant TRX-1 29 WheelSystem
TIRES	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared

GEOMETRY

FRAME	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	425	435	460
Seat Tube Angle	77.0° 77.8°	77.0° 77.8°	77.0° 77.8°
Top Tube Length (mm)	558 557	574 573	599 597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44
Trail (mm)	122 117	122 117	122 117
Wheelbase (mm)	1160 1160	1177 1176	1205 1204
Chain Stay Length (mm)	438 435	438 435	438 435
Bottom Bracket Drop (mm)	40 30	40 30	40 30
Stack (mm)	620 614	625 618	639 632
Reach (mm)	415 424	430 438	451 460
Stand Over Height (mm)	731 740	737 746	756 765
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	29"	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.