

# INTRIGUE ADVANCED PRO 29 0



## SPECS

RAMME	
STØRRELSE	S, M, L
FARGE	Supernova
RAMME	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
GAFFEL	Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
DEMPER	Fox Float DPX2 Factory Live Valve [185/50], custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact SLR TR35, 780x35
STYRSTEM	Giant Contact SL 35
SETEPINNE	Fox Transfer Factory dropper, Shimano remote lever, 30.9
SADEL	Liv Sylvia SL
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano Deore XT
FRONTGIR	N/A
BAKGIR	Shimano XTR
BREMSE	Shimano Deore XT
BREMSEHENDLER	Shimano Deore XT
KASSETT	Shimano Deore XT, 10x51
KJEDE	Shimano
KRANK	Shimano Deore XT, 30t with MRP AMg V2 carbon guide
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant TRX-1 29 WheelSystem
NAV	Giant TRX-1 29 WheelSystem
EIKE	Giant TRX-1 29 WheelSystem
DEKK	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared

## GEOMETRI

RAMME	S	M	L
	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	425	435	460
Seat Tube Angle	77,0°   77,8°	77,0°   77,8°	77,0°   77,8°
Top Tube Length (mm)	558   557	574   573	599   597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°
Fork Rake (mm)	44	44	44
Trail (mm)	122   117	122   117	122   117
Wheelbase (mm)	1160   1160	1177   1176	1205   1204
Chain Stay Length (mm)	438   435	438   435	438   435
Bottom Bracket Drop (mm)	40   30	40   30	40   30
Stack (mm)	620   614	625   618	639   632
Reach (mm)	415   424	430   438	451   460
Stand Over Height (mm)	731   740	737   746	756   765
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.