

# INTRIGUE ADVANCED PRO 29 0



## SPECIFIKACIJE

| OKVIR               |                                                                                                                  |
|---------------------|------------------------------------------------------------------------------------------------------------------|
| VELIKOSTI           | S, M, L                                                                                                          |
| BARVE               | Supernova                                                                                                        |
| OKVIR               | Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip                           |
| VILICE              | Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv |
| AMORTIZER           | Fox Float DPX2 Factory Live Valve [185/50], custom tuned for Liv                                                 |
| KOMPONENTE          |                                                                                                                  |
| KRMILO              | Giant Contact SLR TR35, 780x35                                                                                   |
| OPORA KRMILA        | Giant Contact SL 35                                                                                              |
| OPORA SEDEŽA        | Fox Transfer Factory dropper, Shimano remote lever, 30.9                                                         |
| SEDEŽ               | Liv Sylvia SL                                                                                                    |
| PEDALA              | N/A                                                                                                              |
| POGON               |                                                                                                                  |
| PRESTAVNE ROČICE    | Shimano Deore XT                                                                                                 |
| PREDNJI MENJALNIK   | N/A                                                                                                              |
| ZADNJI MENJALNIK    | Shimano XTR                                                                                                      |
| ZAVORE              | Shimano Deore XT                                                                                                 |
| ZAVORNE ROČICE      | Shimano Deore XT                                                                                                 |
| VERIŽNIK            | Shimano Deore XT, 10x51                                                                                          |
| VERIGA              | Shimano                                                                                                          |
| GONILKE Z VERIŽNIKI | Shimano Deore XT, 30t with MRP AMg V2 carbon guide                                                               |
| BOTTOM BRACKET      | Shimano, press fit                                                                                               |

| OBROČNIKI |                                                                                                                                |
|-----------|--------------------------------------------------------------------------------------------------------------------------------|
| OBROČI    | Giant TRX-1 29 WheelSystem                                                                                                     |
| PESTA     | Giant TRX-1 29 WheelSystem                                                                                                     |
| NAPERE    | Giant TRX-1 29 WheelSystem                                                                                                     |
| PLAŠČI    | [F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| DODATKI   | tubeless prepared                                                                                                              |

## GEOMETRIJA

| OKVIR                                        | S             |      | M             |      | L             |      |
|----------------------------------------------|---------------|------|---------------|------|---------------|------|
|                                              | LOW           | HIGH | LOW           | HIGH | LOW           | HIGH |
| Dolžina sedežne cevi (mm)                    | 425           |      | 435           |      | 460           |      |
| Kot sedežne cevi                             | 77,0°   77,8° |      | 77,0°   77,8° |      | 77,0°   77,8° |      |
| Top Tube Length (mm)                         | 558   557     |      | 574   573     |      | 599   597     |      |
| Višina glave okvirja (mm)                    | 105           |      | 110           |      | 125           |      |
| Krmilni kot                                  | 65,8°   66,5° |      | 65,8°   66,5° |      | 65,8°   66,5° |      |
| Zamik vpetja osi (mm)                        | 44            |      | 44            |      | 44            |      |
| Trail (mm)                                   | 122   117     |      | 122   117     |      | 122   117     |      |
| Medosna razdalja (mm)                        | 1160   1160   |      | 1177   1176   |      | 1205   1204   |      |
| Dolžina cevi ob verigi (mm)                  | 438   435     |      | 438   435     |      | 438   435     |      |
| Bottom Bracket Drop (mm)                     | 40   30       |      | 40   30       |      | 40   30       |      |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 620   614     |      | 625   618     |      | 639   632     |      |
| Doseg (mm)                                   | 415   424     |      | 430   438     |      | 451   460     |      |
| Višina zgornje cevi (mm)                     | 731   740     |      | 737   746     |      | 756   765     |      |
| Širina krmila (mm)                           | 760           |      | 760           |      | 780           |      |
| Dolžina opore krmila (mm)                    | 50            |      | 50            |      | 50            |      |
| Dolžina gonilke (mm)                         | 170           |      | 170           |      | 175           |      |
| Velikost obročnikov                          | 29"           |      | 29"           |      | 29"           |      |

Vse navedene specifikacije se lahko spremenijo brez obvestila.