

# INTRIGUE ADVANCED PRO 29 1



## SPECS

FRAME	
<b>SIZES</b>	S, M, L
<b>COLOURS</b>	Messier/Carbon
<b>FRAME</b>	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
<b>FORK</b>	Fox 34 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
<b>SHOCK</b>	Fox Factory Live, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR TR35
<b>GRIPS</b>	Liv Tactal single lock-on
<b>STEM</b>	Giant Contact SL
<b>SEATPOST</b>	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM GX Eagle, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM GX Eagle
<b>BRAKES</b>	Shimano Deore XT M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano Deore XT, BL-M8100
<b>CASSETTE</b>	SRAM GX, 10x52
<b>CHAIN</b>	SRAM GX Eagle
<b>CRANKSET</b>	SRAM GX Eagle DUB, 30t
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
<b>SPOKES</b>	Sapim
<b>TIRES</b>	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
<b>EXTRAS</b>	Tubeless prepared, max tyre size 2.5", max chainring size 32t

**Price: \$8,999.00**

## GEOMETRY

FRAME	S	M	L
	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	425	435	460
Seat Tube Angle	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°
Top Tube Length (mm)	558   557	574   573	599   597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°
Fork Rake (mm)	44	44	44
Trail (mm)	122   117	122   117	122   117
Wheelbase (mm)	1160   1160	1177   1176	1205   1204
Chain Stay Length (mm)	438   435	438   435	438   435
Bottom Bracket Drop (mm)	40   30	40   30	40   30
Stack (mm)	620   614	625   618	639   632
Reach (mm)	415   424	430   438	451   460
Stand Over Height (mm)	742   751	732   741	751   759
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	29"	29"	29"

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.