



SPECS

RAMME	
STØRRELSE	S, M, L
FARGE	Dark Iridescent
RAMME	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
GAFFEL	RockShox Pike Select, 140mm, Boost, 15x110 Maxle Stealth, tapered, 42mm offset, custom tuned for Liv
DEMPER	RockShox Deluxe Select+ [185/50], RT, custom tuned for Liv
KOMPONENTER	
STYRE	Giant Contact TR35, 780x35
STYRSTEM	Giant Contact SL 35
SETEPINNE	Giant Contact Switch dropper, remote lever, 30.9
SADEL	Liv Sylvia SL
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM NX Eagle
FRONTGIR	N/A
BAKGIR	SRAM NX Eagle
BREMSER	Shimano MT520, hydraulic disc
BREMSEHENDLER	Shimano MT501
KASSETT	SRAM NX Eagle, 11x50
KJEDE	SRAM NX Eagle
KRANK	TruVativ Descendent 6k Eagle DUB, 30t
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant TRX-2 29 WheelSystem
NAV	Giant TRX-2 29 WheelSystem
EIKE	Giant TRX-2 29 WheelSystem
DEKK	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared

GEOMETRI

RAMME	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	425	435	460
Seat Tube Angle	77,0° 77,8°	77,0° 77,8°	77,0° 77,8°
Top Tube Length (mm)	558 557	574 573	599 597
Head Tube Length (mm)	105	110	125
Head Tube Angle	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44
Trail (mm)	122 117	122 117	122 117
Wheelbase (mm)	1160 1160	1177 1176	1205 1204
Chain Stay Length (mm)	438 435	438 435	438 435
Bottom Bracket Drop (mm)	40 30	40 30	40 30
Stack (mm)	620 614	625 618	639 632
Reach (mm)	415 424	430 438	451 460
Stand Over Height (mm)	731 740	737 746	756 765
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	175
Wheel Size	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.