

INTRIGUE ADVANCED PRO 29 2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L
BARVE	Dark Iridescent
OKVIR	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
VILICE	RockShox Pike Select, 140mm, Boost, 15x110 Maxle Stealth, tapered, 42mm offset, custom tuned for Liv
AMORTIZER	RockShox Deluxe Select+ [185/50], RT, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, 780x35
OPORA KRMILA	Giant Contact SL 35
OPORA SEDEŽA	Giant Contact Switch dropper, remote lever, 30.9
SEDEŽ	Liv Sylvia SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM NX Eagle
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM NX Eagle
ZAVORE	Shimano MT520, hydraulic disc
ZAVORNE ROČICE	Shimano MT501
VERIŽNIK	SRAM NX Eagle, 11x50
VERIGA	SRAM NX Eagle
GONILKE Z VERIŽNIKI	TruVativ Descendent 6k Eagle DUB, 30t
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TRX-2 29 WheelSystem
PESTA	Giant TRX-2 29 WheelSystem
NAPERE	Giant TRX-2 29 WheelSystem
PLAŠČI	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	tubeless prepared

GEOMETRIJA

OKVIR	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	425		435		460	
Kot sedežne cevi	77,0° 77,8°		77,0° 77,8°		77,0° 77,8°	
Top Tube Length (mm)	558 557		574 573		599 597	
Višina glave okvirja (mm)	105		110		125	
Krmilni kot	65,8° 66,5°		65,8° 66,5°		65,8° 66,5°	
Zamik vpetja osi (mm)	44		44		44	
Trail (mm)	122 117		122 117		122 117	
Medosna razdalja (mm)	1160 1160		1177 1176		1205 1204	
Dolžina cevi ob verigi (mm)	438 435		438 435		438 435	
Bottom Bracket Drop (mm)	40 30		40 30		40 30	
Oddaljenost zgornje cevi od gonilne osi (mm)	620 614		625 618		639 632	
Doseg (mm)	415 424		430 438		451 460	
Višina zgornje cevi (mm)	731 740		737 746		756 765	
Širina krmila (mm)	760		760		780	
Dolžina opore krmila (mm)	50		50		50	
Dolžina gonilke (mm)	170		170		175	
Velikost obročnikov	29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.