INTRIGUE LT 1



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S: MX only M, L: 29"" F&R out of the box, MX compatible
ЦВЯТ	Soap Suds
РАМКА	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
ВИЛКА	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
ЗАДЕН АМОРТИСЬОР	Fox Float DPS Performance 185/55, custom tuned for Liv
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
ГРИПОВЕ	Liv Tactal Pro Single Lock-On XS/S: 110mm, M/L: 120mm
ЛАПА	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9
СЕДАЛКА	Liv Sylvia
ПЕДАЛИ	platform
DRIVETRAIN	
КОМАНДИ	Shimano SLX M7100 , 1x12
ПРЕДЕН ДЕРАЙЛЬОР	N/A
ЗАДЕН ДЕРАЙЛЬОР	Shimano SLX M7100, Shadow +
СПИРАЧКИ	Tektro M750, Hydraulic Disc [F] 203mm [R] 180mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Tektro HDM-750
КАСЕТА	Shimano Deore, 10x51
ВЕРИГА	KMC X-12
КУРБЕЛ	Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
ГЛАВИНИ	alloy
СПИЦИ	stainless
ГУМИ	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
ЕКСТРИ	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	370	390	420	450
Seat Tube Angle	76,2° | 76,6° | 77,0°	76,2° | 76,6° | 77,0°	77,3° | 77,6° | 78,0°	77,3° | 77,6° | 78,0
Top Tube Length (mm)	552 | 552 | 550	567 | 566 | 565	581 | 580 | 579	603 | 602 | 601
Head Tube Length (mm)	95	95	100	110
Head Tube Angle	64,7° | 65,1° | 65,5°	64,6° | 65,1° | 65,5°	64,8° | 65,1° | 65,5°	64,8° | 65,1° | 65,5
Fork Rake (mm)	44	44	44	44
Trail (mm)	131 | 127,9 | 124,8	131,6 | 127,8 | 124,8	130,6 | 127,7 | 124,8	130,5 | 127,7 | 124
Wheelbase (mm)	1166 | 1166 | 1164	1183 | 1180 | 1179	1208 | 1207 | 1207	1232 | 1231 | 123
Chain Stay Length (mm)	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440
Bottom Bracket Drop (mm)	25 | 20 | 15	24 | 20 | 15	35 | 30 | 25	35 | 30 | 25
Stack (mm)	629 | 627 | 624	628 | 627 | 624	628 | 625 | 622	637 | 634 | 631
Обсег (mm)	398 | 402 | 406	413 | 417 | 421	439 | 442 | 447	459 | 462 | 467
Stand Over Height (mm)	727 | 727 | 727	750 | 750 | 750	760 | 760 | 760	770 | 770 | 770
Ширина на Кормило (mm)	760	760	760	780
Дължина на Лапа (mm)	40	50	50	50
Дължина на Курбел (mm)	165	170	170	170
Размер на Каплите	F29"/R27.5	F29"/R27.5	29"	29"

All specifications listed are subject to change without notice.