

INTRIGUE LT 1



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
ΧΡΩΜΑΤΑ	Soap Suds
ΣΚΕΛΕΤΟΣ	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
ΠΙΡΟΥΝΙ	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
ΑΝΑΡΤΗΣΗ	Fox Float Performance 185x55, custom tuned for Liv
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	Giant Contact Switch dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
Σ'ΕΛΛΑ	Liv Sylvia
ΠΕΝΤΑΛ	platform
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Deore, 1x12
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Deore, Shadow +
ΦΡΕΝΑ	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ΜΑΝΙΤΕΤΣ ΦΡΕΝΩΝ	Shimano BL-MT401
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano Deore M6100, 10x51
ΑΛΥΣΙΔΑ	KMC X12
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
ΚΕΝΤΡΑ	alloy
ΑΚΤΙΝΕΣ	stainless
ΕΛΑΣΤΙΚΑ	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	600
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	630
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	466
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712	750	750	750
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F 29 R 27.5			F 29 R 27.5			29"			29"		

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση