

INTRIGUE LT 1



SPECS

FRAME	
SIZES	XS, S: (F 29"/R27.5"), M, L: (F/R 29" MX compatible)
COLOURS	Soap Suds
FRAME	ALUXX SL-Grade aluminium front and rear triangles, 150mm Maestro Suspension, flip chip 3 position, integrated downtube storage, 55mm Chain line
FORK	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
SHOCK	Fox Float DPS Performance 185/55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact, 35mm
GRIPS	Liv Tactal single lock-on
STEM	Giant Contact SL
SEATPOST	Giant Contact Switch dropper, remote
SADDLE	Liv Sylvia
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX M7100 , 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M7100, Shadow +
BRAKES	Tektro M750, hydraulic, Tektro rotors [F]203mm, [R]180mm
BRAKE LEVERS	Tektro HDM-750
CASSETTE	Shimano Deore, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano M5121, 30t, 55mm chainline
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
HUBS	Alloy
SPOKES	Stainless
TIRES	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tyre size 2.5", max chainring size 32t

Price: \$4,799.00

GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Tube Angle	76.2°	76.6°	77.0°	76.2°	76.6°	77.0°	77.3°	77.6°	78.0°	77.3°	77.6°	78.0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	601
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64.7°	65.1°	65.5°	64.6°	65.1°	65.5°	64.8°	65.1°	65.5°	64.8°	65.1°	65.5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127.9	124.8	131.6	127.8	124.8	130.6	127.7	124.8	130.5	127.7	124.8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1231
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	631
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	467
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712	750	750	750
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F29"/R27.5			F29"/R27.5			29"			29"		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are