

INTRIGUE LT 1



SPECS

FRAME	
SIZES	XS, S: MX only M, L: 29" F&R out of the box, MX compatible
COLORS	Soap Suds
FRAME	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
FORK	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
SHOCK	Fox Float DPS Performance 185/55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 110mm, M/L: 120mm
STEM	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
SEATPOST	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano SLX M7100 , 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M7100, Shadow +
BRAKES	Tektro M750, Hydraulic Disc [F] 203mm [R] 180mm
BRAKE LEVERS	Tektro HDM-750
CASSETTE	Shimano Deore, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
HUBS	alloy
SPOKES	stainless
TIRES	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

Price: ₹ 4,199.00

GEOMETRY

FRAME	S	M	L
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	390	420	450
Seat Tube Angle	76.2° 76.6° 77.0°	77.3° 77.6° 78.0°	77.3° 77.6° 78.0°
Top Tube Length (mm)	567 566 565	581 580 579	603 602 601
Head Tube Length (mm)	95	100	110
Head Tube Angle	64.6° 65.1° 65.5°	64.8° 65.1° 65.5°	64.8° 65.1° 65.5°
Fork Rake (mm)	44	44	44
Trail (mm)	131.6 127.8 124.8	130.6 127.7 124.8	130.5 127.7 124.8
Wheelbase (mm)	1183 1180 1179	1208 1207 1207	1232 1231 1231
Chain Stay Length (mm)	443 442 440	443 442 440	443 442 440
Bottom Bracket Drop (mm)	24 20 15	35 30 25	35 30 25
Stack (mm)	628 627 624	628 625 622	637 634 631
Reach (mm)	413 417 421	439 442 447	459 462 467
Stand Over Height (mm)	750 750 750	760 760 760	770 770 770
Handlebar Width (mm)	760	760	780
Stem Length (mm)	50	50	50
Crank Length (mm)	170	170	170
Wheel Size	F29"/R27.5	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.