

INTRIGUE LT 1



TECHNIQUES

| CADRE | |
|---------------------|--|
| TAILLES | XS, S: MX only M, L: 29" F&R out of the box, MX compatible |
| COLORIS | Soap Suds |
| CADRE | ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage |
| FOURCHE | Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv |
| AMORTISSEUR | Fox Float DPS Performance 185/55, custom tuned for Liv |
| COMPOSANTS | |
| CINTRE | Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm |
| POIGNÉES | Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm |
| POTENCE | Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm |
| TIGE DE SELLE | Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9 x 440mm |
| SELLE | Liv Sylvia |
| PÉDALES | platform |
| DÉRAILLEUR | |
| MANETTES | Shimano SLX M7100, 1x12 |
| DÉRAILLEUR AVANT | N/A |
| DÉRAILLEUR ARRIÈRE | Shimano SLX M7100, Shadow + |
| FREINS | Tektro M750 [F] 203mm [R] 180mm |
| LEVIERS DE FREIN | Tektro - 1401-HDM750 |
| CASSETTE | Shimano Deore, 10x51 |
| CHAÎNE | KMC X-12 |
| PÉDALIER | Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm |
| BOITIER DE PÉDALIER | Shimano, press fit |

| ROUES | |
|-------------|--|
| JANTES | Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29 |
| MOYEURS | alloy |
| RAYONS | stainless |
| PNEUS | [F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| EXTRAS | MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t |
| ACCESSOIRES | |
| ECLAIRAGE | Kit d'éclairage avant et arrière à piles |

Prix Public Conseillé: 4 100,00 €

GÉOMÉTRIE

| CADRE | XS | | | S | | | M | | | L | | |
|------------------------------------|------------|-------|-------|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH | LOW | MID | HIGH |
| Longueur de tube de selle (mm) | 370 | | | 390 | | | 420 | | | 450 | | |
| Angle de tube de selle | 76,2° | 76,6° | 77,0° | 76,2° | 76,6° | 77,0° | 77,3° | 77,6° | 78,0° | 77,3° | 77,3° | 77,3° |
| Longueur du tube supérieur (mm) | 552 | 552 | 550 | 567 | 566 | 565 | 581 | 580 | 579 | 603 | 602 | 602 |
| Longueur du tube de direction (mm) | 95 | | | 95 | | | 100 | | | 110 | | |
| Angle du tube de direction | 64,7° | 65,1° | 65,5° | 64,6° | 65,1° | 65,5° | 64,8° | 65,1° | 65,5° | 64,8° | 65,5° | 65,5° |
| Déport de fourche (mm) | 44 | | | 44 | | | 44 | | | 44 | | |
| Trail (mm) | 131 | 127,9 | 124,8 | 131,6 | 127,8 | 124,8 | 130,6 | 127,7 | 124,8 | 130,5 | 127,7 | 124,8 |
| Empattement (mm) | 1166 | 1166 | 1164 | 1183 | 1180 | 1179 | 1208 | 1207 | 1207 | 1232 | 1232 | 1232 |
| Longueur des bases (mm) | 443 | 442 | 440 | 443 | 442 | 440 | 443 | 442 | 440 | 443 | 442 | 442 |
| Drop du boîtier de pédalier (mm) | 25 | 20 | 15 | 24 | 20 | 15 | 35 | 30 | 25 | 35 | 30 | 25 |
| Stack (mm) | 629 | 627 | 624 | 628 | 627 | 624 | 628 | 625 | 622 | 637 | 634 | 634 |
| Reach (mm) | 398 | 402 | 406 | 413 | 417 | 421 | 439 | 442 | 447 | 459 | 462 | 462 |
| Hauteur en statique (mm) | 727 | 727 | 727 | 750 | 750 | 750 | 760 | 760 | 760 | 770 | 770 | 770 |
| Largeur de cintre (mm) | 760 | | | 760 | | | 760 | | | 780 | | |
| Longueur de potence (mm) | 40 | | | 50 | | | 50 | | | 50 | | |
| Longueur des manivelles (mm) | 165 | | | 170 | | | 170 | | | 170 | | |
| Diamètre des roues | F29"/R27.5 | | | F29"/R27.5 | | | 29" | | | 29" | | |

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.