

INTRIGUE LT 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
BOJE	Soap Suds
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VILICA	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
AMORTIZER	Fox Float Performance 185x55, custom tuned for Liv
KOMPONENTE	
VOLAN	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
LULA VOLANA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
CIJEV SJEDALA	Giant Contact Switch dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SJEDALO	Liv Sylvia
PEDALE	platform
POGON	
RUČICE MJENJAČA	Shimano Deore, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	Shimano Deore, Shadow +
KOČNICE	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
RUČICE KOČNICA	Shimano BL-MT401
KAZETA	Shimano Deore M6100, 10x51
LANAC	KMC X12
POGON	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
OSOVINA POGONA (BB)	Praxis, press fit

KOTAČI	
OBRUČI	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NABE	alloy
ŽBICE	stainless
GUME	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODACI	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	XS			S		
	LOW	MID	HIGH	LOW	MID	HIGH
Dužina cijevi sjedala (mm)	370			390		
Seat Post Insertion Depth (mm)	230			250		
Kut cijevi sjedala	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°		
Dužina gornje cijevi (mm)	552	552	550	567	566	565
Dužina prednje cijevi (mm)	95			95		
Kut vilice	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°		
Zakrivljenost vilice (offset) (mm)	44			44		
Staza (mm)	131	127,9	124,8	131,6	127,8	124,8
Međuosovinski razmak kotača (mm)	1166	1166	1164	1183	1180	1179
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	443	442	440	443	442	440
Položaj osovine pogona (mm)	25	20	15	24	20	15
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	629	627	624	628	627	624
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	398	402	406	413	417	421
Prekoračna visina (mm)	613	613	613	674	674	674
Širina volana (mm)	760			760		
Dužina lule volana (mm)	40			50		
Dužina poluge pedale (mm)	165			170		
Veličina kotača	F 29 R 27.5			F 29 R 27.5		

Sve navedene specifikacije podložne su promjeni bez prethodne najave.