

INTRIGUE LT 1



SPECS

RAMME	
STØRRELSE	XS, S: MX only M, L: 29" F&R out of the box, MX compatible
FARGE	Soap Suds
RAMME	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
GAFFEL	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
DEMPER	Fox Float DPS Performance 185/55, custom tuned for Liv
KOMponenter	
STYRE	Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 110mm, M/L: 120mm
STYRSTEM	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
SETEPINNE	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9
SADEL	Liv Sylvia
PEDALER	platform
DRIVVERK	
GIRHENDLER	Shimano SLX M7100 , 1x12
FRONTGIR	N/A
BAKGIR	Shimano SLX M7100, Shadow +
BREMSER	Tektro M750, Hydraulic Disc [F] 203mm [R] 180mm
BREMSEHENDLER	Tektro HDM-750
KASSETT	Shimano Deore, 10x51
KJEDE	KMC X-12
KRANK	Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
NAV	alloy
EIKE	stainless
DEKK	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRI

RAMME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	78,0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	601
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	65,5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	124,8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1231
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	631
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	467
Stand Over Height (mm)	727	727	727	750	750	750	760	760	760	770	770	770
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F29"/R27.5			F29"/R27.5			29"			29"		

Alle spesifikasjonene kan endres uten varsel.