

# INTRIGUE LT 1



## SPECS

FRAME	
<b>SIZES</b>	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
<b>COLORS</b>	Soap Suds
<b>FRAME</b>	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
<b>FORK</b>	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
<b>SHOCK</b>	Fox Float Performance 185x55, custom tuned for Liv
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
<b>GRIPS</b>	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
<b>STEM</b>	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
<b>SEATPOST</b>	Giant Contact Switch dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	platform
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore, Shadow +
<b>BRAKES</b>	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano BL-MT401
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X12
<b>CRANKSET</b>	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
<b>BOTTOM BRACKET</b>	Praxis, press fit

WHEELS	
<b>RIMS</b>	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
<b>HUBS</b>	alloy
<b>SPOKES</b>	stainless
<b>TIRES</b>	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
<b>EXTRAS</b>	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

## GEOMETRY

FRAME	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	78,0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	600
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	65,5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	124,8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1231
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	633
Reach (mm)	398	402	406	413	417	421	439	442	447	459	462	466
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712	750	750	750
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F 29   R 27.5			F 29   R 27.5			29"			29"		

All specifications listed are subject to change without notice.