

# INTRIGUE LT 1



## SPECS

| CADRU                             |   |
|-----------------------------------|---|
| <b>MARIMI</b>                     | XS, S: MX only, M, L: 29" F&R out of the box, MX compatible   |
| <b>CULORI</b>                     | Soap Suds   |
| <b>CADRU</b>                      | ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage                                       |
| <b>FURCA</b>                      | Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset  |
| <b>SOC</b>                        | Fox Float Performance 185x55, custom tuned for Liv  |
| COMPONENTE                        |   |
| <b>GHIDON</b>                     | Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm  |
| <b>GRIPS</b>                      | Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm   |
| <b>PIPA</b>                       | Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm  |
| <b>TIJA SA</b>                    | Giant Contact Switch dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm |
| <b>SA</b>                         | Liv Sylvia  |
| <b>PEDALE</b>                     | platform  |
| SISTEMUL DE SCHIMBARE A VITEZELOR |   |
| <b>MANETE SCHIMBATOR</b>          | Shimano Deore, 1x12   |
| <b>SCHIMBATOR FATA</b>            | N/A   |
| <b>SCHIMBATOR SPATE</b>           | Shimano Deore, Shadow +   |
| <b>FRANE</b>                      | Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm  |
| <b>MANETE FRANA</b>               | Shimano BL-MT401  |
| <b>PINIOANE</b>                   | Shimano Deore M6100, 10x51  |
| <b>LANT</b>                       | KMC X12   |
| <b>ANGRENAJ</b>                   | Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm   |
| <b>BOTTOM BRACKET</b>             | Praxis, press fit   |

| ROTI            |  |
|-----------------|--|
| <b>JANTE</b>    | Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29  |
| <b>BUTUCI</b>   | alloy  |
| <b>SPITE</b>    | stainless  |
| <b>ANVELOPE</b> | Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless |
| <b>EXTRAS</b>   | MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t  |

## GEOMETRIE

| CADRU                          | XS            |       |       | S             |       |       | M     |       |       | L     |       |       |
|--------------------------------|---------------|-------|-------|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
|                                | LOW           | MID   | HIGH  | LOW           | MID   | HIGH  | LOW   | MID   | HIGH  | LOW   | MID   | HIGH  |
| Seat Tube Length (mm)          | 370           |       |       | 390           |       |       | 420   |       |       | 450   |       |       |
| Seat Post Insertion Depth (mm) | 230           |       |       | 250           |       |       | 280   |       |       | 310   |       |       |
| Seat Tube Angle                | 76,2°         | 76,6° | 77,0° | 76,2°         | 76,6° | 77,0° | 77,3° | 77,6° | 78,0° | 77,3° | 77,6° | 78,0° |
| Top Tube Length (mm)           | 552           | 552   | 550   | 567           | 566   | 565   | 581   | 580   | 579   | 603   | 602   | 600   |
| Head Tube Length (mm)          | 95            |       |       | 95            |       |       | 100   |       |       | 110   |       |       |
| Head Tube Angle                | 64,7°         | 65,1° | 65,5° | 64,6°         | 65,1° | 65,5° | 64,8° | 65,1° | 65,5° | 64,8° | 65,1° | 65,5° |
| Fork Rake (mm)                 | 44            |       |       | 44            |       |       | 44    |       |       | 44    |       |       |
| Trail (mm)                     | 131           | 127,9 | 124,8 | 131,6         | 127,8 | 124,8 | 130,6 | 127,7 | 124,8 | 130,5 | 127,7 | 124,8 |
| Wheelbase (mm)                 | 1166          | 1166  | 1164  | 1183          | 1180  | 1179  | 1208  | 1207  | 1207  | 1232  | 1231  | 1231  |
| Chain Stay Length (mm)         | 443           | 442   | 440   | 443           | 442   | 440   | 443   | 442   | 440   | 443   | 442   | 440   |
| Bottom Bracket Drop (mm)       | 25            | 20    | 15    | 24            | 20    | 15    | 35    | 30    | 25    | 35    | 30    | 25    |
| Stack (mm)                     | 629           | 627   | 624   | 628           | 627   | 624   | 628   | 625   | 622   | 637   | 634   | 633   |
| Reach (mm)                     | 398           | 402   | 406   | 413           | 417   | 421   | 439   | 442   | 447   | 459   | 462   | 466   |
| Stand Over Height (mm)         | 613           | 613   | 613   | 674           | 674   | 674   | 712   | 712   | 712   | 750   | 750   | 750   |
| Handlebar Width (mm)           | 760           |       |       | 760           |       |       | 760   |       |       | 780   |       |       |
| Stem Length (mm)               | 40            |       |       | 50            |       |       | 50    |       |       | 50    |       |       |
| Crank Length (mm)              | 165           |       |       | 170           |       |       | 170   |       |       | 170   |       |       |
| Wheel Size                     | F 29   R 27.5 |       |       | F 29   R 27.5 |       |       | 29"   |       |       | 29"   |       |       |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.