

INTRIGUE LT 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S: MX only M, L: 29" F&R out of the box, MX compatible
FARBY	Soap Suds
RÁM	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
VIDLICA	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
TLMIČ	Fox Float DPS Performance 185/55, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-On XS/S: 110mm, M/L: 120mm
PREDSTAVEC	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
SEDLOVKA	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	Shimano SLX M7100 , 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano SLX M7100, Shadow +
BRZDY	Tektro M750, Hydraulic Disc [F] 203mm [R] 180mm
BRZDOVÉ PÁKY	Tektro HDM-750
KAZETA	Shimano Deore, 10x51
REŤAZ	KMC X-12
KLUKY	Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
NÁBOJE	alloy
ŠPICE	stainless
PNEUMATIKY	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

Cena: 3 989 € (pôvodná cena 4 199 €)

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Uhol sedlovej trubky	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°
Dĺžka hornej rámovej trubky (mm)	552	552	550	567	566	565	581	580	579
Dĺžka hlavovej trubky (mm)	95			95			100		
Uhol hlavovej trubky	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°
Offset vidlice (mm)	44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8
Rázvor (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Dĺžka zadnej stavby (mm)	443	442	440	443	442	440	443	442	440
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25	20	15	24	20	15	35	30	25
Stack - výška riadenia (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Výška rámu od zeme (mm)	727	727	727	750	750	750	760	760	760
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	F29"/R27.5			F29"/R27.5			29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.