

INTRIGUE LT 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
FARBY	Soap Suds
RÁM	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
VIDLICA	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
TLMIČ	Fox Float Performance 185x55, custom tuned for Liv
KOMONENTY	
RIADIDLÁ	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
PREDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDLOVKA	Giant Contact Switch dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	Shimano Deore, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano Deore, Shadow +
BRZDY	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano BL-MT401
KAZETA	Shimano Deore M6100, 10x51
REŤAZ	KMC X12
KLUKY	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
STREDOVÉ ZLOŽENIE	Praxis, press fit

KOLESÁ	
RÁFIKY	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NÁBOJE	alloy
ŠPICE	stainless
PNEUMATIKY	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

Cena: 3 999 €

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Hĺbka vloženia sedlovky (mm)	230			250			280		
Uhol sedlovej trubky	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°
Dĺžka hornej rámovej trubky (mm)	552	552	550	567	566	565	581	580	579
Dĺžka hlavovej trubky (mm)	95			95			100		
Uhol hlavovej trubky	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°
Offset vidlice (mm)	44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8
Rázvor (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Dĺžka zadnej stavby (mm)	443	442	440	443	442	440	443	442	440
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25	20	15	24	20	15	35	30	25
Stack - výška riadenia (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Výška rámu od zeme (mm)	613	613	613	674	674	674	712	712	712
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	F 29	R 27.5		F 29	R 27.5		29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.