

INTRIGUE LT 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S: MX only M, L: 29" F&R out of the box, MX compatible
BARVE	Soap Suds
OKVIR	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
VILICE	Fox 36 Float Performance, 160mm, Grip damper, Boost, 15x110, Kabolt X, tapered, 44mm offset, custom tuned for Liv
AMORTIZER	Fox Float DPS Performance 185/55, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 110mm, M/L: 120mm
OPORA KRMILA	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M/L: 150mm travel / 30.9
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano SLX M7100 , 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX M7100, Shadow +
ZAVORE	Tektro M750, Hydraulic Disc [F] 203mm [R] 180mm
ZAVORNE ROČICE	Tektro HDM-750
VERIŽNIK	Shimano Deore, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Shimano M511, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
PESTA	alloy
NAPERE	stainless
PLAŠČI	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	XS			S			M			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	L
Dolžina sedežne cevi (mm)	370			390			420			4
Kot sedežne cevi	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	7
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	6
Višina glave okvirja (mm)	95			95			100			1
Krmilni kot	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	6
Zamik vpetja osi (mm)	44			44			44			4
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	1
Medosna razdalja (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1
Dolžina cevi ob verigi (mm)	443	442	440	443	442	440	443	442	440	4
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	3
Oddaljenost zgornje cevi od gonilne osi (mm)	629	627	624	628	627	624	628	625	622	6
Doseg (mm)	398	402	406	413	417	421	439	442	447	4
Višina zgornje cevi (mm)	727	727	727	750	750	750	760	760	760	7
Širina krmila (mm)	760			760			760			7
Dolžina opore krmila (mm)	40			50			50			5
Dolžina gonilke (mm)	165			170			170			1
Velikost obročnikov	F29"/R27.5			F29"/R27.5			29"			2

Vse navedene specifikacije se lahko spremenijo brez obvestila.