

INTRIGUE LT 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
BARVE	Soap Suds
OKVIR	ALUXX SL-grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VILICE	Marzocchi Bomber Z1, 160mm, Rail damper, Boost 15x110 Kabolt, tapered, 44mm offset
AMORTIZER	Fox Float Performance 185x55, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 35mm, 20mm rise XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
OPORA KRMILA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote XS: 125mm travel/ 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano Deore, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore, Shadow +
ZAVORE	Shimano BR-MT420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano BL-MT401
VERIŽNIK	Shimano Deore M6100, 10x51
VERIGA	KMC X12
GONILKE Z VERIŽNIKI	Praxis Cadet, steel chain ring 30t, 52mm chainline S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI	
OBROČI	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
PESTA	alloy
NAPERE	stainless
PLAŠČI	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DODATKI	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	XS			S			M			L
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	L
Dolžina sedežne cevi (mm)	370			390			420			4
Seat Post Insertion Depth (mm)	230			250			280			3
Kot sedežne cevi	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	7
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	6
Višina glave okvirja (mm)	95			95			100			1
Krmilni kot	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	6
Zamik vpetja osi (mm)	44			44			44			4
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	1
Medosna razdalja (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1
Dolžina cevi ob verigi (mm)	443	442	440	443	442	440	443	442	440	4
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	3
Oddaljenost zgornje cevi od gonilne osi (mm)	629	627	624	628	627	624	628	625	622	6
Doseg (mm)	398	402	406	413	417	421	439	442	447	4
Višina zgornje cevi (mm)	613	613	613	674	674	674	712	712	712	7
Širina krmila (mm)	760			760			760			7
Dolžina opore krmila (mm)	40			50			50			5
Dolžina gonilke (mm)	165			170			170			1
Velikost obročnikov	F 29	R 27.5		F 29	R 27.5		29"			2

Vse navedene specifikacije se lahko spremenijo brez obvestila.