INTRIGUE LT 2



SPECS

ΣΚΕΛΕΤΌΣ	
ΜΕΓΈΘΗ	XS, S: MX only M, L: 29"" F&R out of the box, MX compatible
ΧΡΏΜΑΤΑ	Aged Denim
ΣΚΕΛΕΤΌΣ	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
ΠΙΡΟΎΝΙ	RockShox 35 Gold RL, 160mm, Motion Control damper, Boost, 15x110, 110 Maxle Stealth, tapered, 44mm offset, custom tuned for Liv
ΑΝΆΡΤΗΣΗ	Fox Float DPS Performance 185/55, custom tuned for Liv
ΕΞΑΡΤΉΜΑΤΑ	
ΤΙΜΌΝΙ	Giant Contact, 35mm XS: 760mm, S:760mm, M:760mm, L:780mm
GRIPS	Liv Tactal single lock-on XS/S: 120mm, M/L: 130mm
ΛΑΙΜΌΣ ΤΙΜΟΝΙΟΎ	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
ΛΑΙΜΌΣ ΣΈΛΛΑΣ	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M & L: 150mm travel / 30.9
ΣΈΛΛΑ	Liv Sylvia
ΠΕΝΤΆΛ	platform
ΜΕΤΆΔΟΣΗ	
ΛΕΒΙΈ ΤΑΧΥΤΉΤΩΝ	SRAM SX Eagle, 1x12
ΝΤΕΡΑΓΙΈΡ ΕΜΠΡΌΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΈΡ ΟΠΊΣΘΙΟ.	SRAM SX Eagle
ΦΡΈΝΑ	Tektro M745, Hydraulic Disc [F] 203mm [R] 180mm
ΜΑΝΈΤΕΣ ΦΡΈΝΩΝ	Tektro HDM-745
CASETTE Ή ΕΛΕΎΘΕΡΟ	SRAM SX Eagle, 11x50
ΑΛΥΣΊΔΑ	SRAM SX Eagle
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	SRAM SX Eagle DUB, 30t, 55mm chainline XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΆΝΙΑ	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
ΚΈΝΤΡΑ	alloy
ΑΚΤΊΝΕΣ	stainless
ΕΛΑΣΤΙΚΆ	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΌΣ	XS	S	M	L
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Seat Tube Length (mm)	370	390	420	450
Seat Tube Angle	76,2° | 76,6° | 77,0°	76,2° | 76,6° | 77,0°	77,3° | 77,6° | 78,0°	77,3° | 77,6° | 78,0
Top Tube Length (mm)	552 | 552 | 550	567 | 566 | 565	581 | 580 | 579	603 | 602 | 601
Head Tube Length (mm)	95	95	100	110
Head Tube Angle	64,7° | 65,1° | 65,5°	64,6° | 65,1° | 65,5°	64,8° | 65,1° | 65,5°	64,8° | 65,1° | 65,5
Fork Rake (mm)	44	44	44	44
Trail (mm)	131 | 127,9 | 124,8	131,6 | 127,8 | 124,8	130,6 | 127,7 | 124,8	130,5 | 127,7 | 124
Wheelbase (mm)	1166 | 1166 | 1164	1183 | 1180 | 1179	1208 | 1207 | 1207	1232 | 1231 | 1231
Chain Stay Length (mm)	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440	443 | 442 | 440
Bottom Bracket Drop (mm)	25 | 20 | 15	24 | 20 | 15	35 | 30 | 25	35 | 30 | 25
Stack (mm)	629 | 627 | 624	628 | 627 | 624	628 | 625 | 622	637 | 634 | 631
Reach (mm)	398 | 402 | 406	413 | 417 | 421	439 | 442 | 447	459 | 462 | 467
Stand Over Height (mm)	727 | 727 | 727	750 | 750 | 750	760 | 760 | 760	770 | 770 | 770
Handlebar Width (mm)	760	760	760	780
Stem Length (mm)	40	50	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	F29"/R27.5	F29"/R27.5	29"	29"

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση