

INTRIGUE LT 2



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S: MX only M, L: 29" F&R out of the box, MX compatible
COLORES	Aged Denim
CUADRO	ALUXX SL-Grade aluminum front and rear triangles, 150mm Maestro Suspension, flip chip, integrated down tube storage
TIJERA	RockShox 35 Gold RL, 160mm, Motion Control damper, Boost, 15x110, 110 Maxle Stealth, tapered, 44mm offset, custom tuned for Liv
AMORTIGUADOR	Fox Float DPS Performance 185/55, custom tuned for Liv
COMPONENTES	
MANUBRIO	Giant Contact, 35mm XS: 760mm, S:760mm, M:760mm, L:780mm
GRIPS	Liv Tactal single lock-on XS/S: 120mm, M/L: 130mm
POTENCIA	Giant Contact TR35, 35mm XS:40mm, S:50mm, M:50mm, L:50mm
POSTE DE ASIENTO	Giant Contact Switch dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 395mm M & L: 150mm travel / 30.9
ASIENTO	Liv Sylvia
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM SX Eagle, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM SX Eagle
FRENOS	Tektro M745, Hydraulic Disc [F] 203mm [R] 180mm
PALANCAS DE FRENOS	Tektro HDM-745
CASSETTE	SRAM SX Eagle, 11x50
CADENA	SRAM SX Eagle
MULTIPLICACIÓN	SRAM SX Eagle DUB, 30t, 55mm chainline XS:165mm, S:170mm, M:170mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F]29, [R]29
MAZAS	alloy
RAYOS	stainless
NEUMÁTICOS	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R, size M and L] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, or [R, size XS and S] Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP AMg CS chainguide, 3M tailgate protector, tubeless prepared, max tire size 2.5", max chainring size 32t

Precio: \$70,900.00

GEOMETRÍA

CUADRO	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longitud de la Base del Poste de Asiento (mm)	370			390			420		
Ángulo de la Base del Poste de Asiento	76.2° 76.6° 77.0°			76.2° 76.6° 77.0°			77.3° 77.6° 78.0°		
Longitud del Tubo Superior (mm)	552	552	550	567	566	565	581	580	579
Longitud del Telescopio (mm)	95			95			100		
Ángulo del Telescopio	64.7° 65.1° 65.5°			64.6° 65.1° 65.5°			64.8° 65.1° 65.5°		
Rake (mm)	44			44			44		
Trail (mm)	131	127.9	124.8	131.6	127.8	124.8	130.6	127.7	124.8
Distancia entre Ejes (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207
Longitud de Vaina Inferior (mm)	443	442	440	443	442	440	443	442	440
Caída del Eje de Centro (mm)	25	20	15	24	20	15	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622
Reach (mm)	398	402	406	413	417	421	439	442	447
Altura del Tubo Superior al Suelo (mm)	727	727	727	750	750	750	760	760	760
Ancho del Manubrio (mm)	760			760			760		
Longitud de la Potencia (mm)	40			50			50		
Longitud de la Biela (mm)	165			170			170		
Tamaño de las Ruedas	F29"/R27.5			F29"/R27.5			29"		

Todas las especificaciones están sujetas a cambios sin previo aviso.