

INTRIGUE LT ADVANCED 1



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
ЦВЯТ	Raw Carbon
РАМКА	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
ВИЛКА	Fox 36 Performance Elite, 160mm, Grip 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Float X Performance Elite 185x55, custom tuned for Liv
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
ГРИПОВЕ	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
ЛАПА	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
КОЛЧЕ ЗА СЕДАЛКА	TranzX travel-adjustable dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
СЕДАЛКА	Liv Sylvia
ПЕДАЛИ	platform
DRIVETRAIN	
КОМАНДИ	SRAM AXS, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM GX T-Type
СПИРАЧКИ	Shimano XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano XT BL-M8100
КАСЕТА	SRAM GX T-Type, 10x52
ВЕРИГА	SRAM GX T-Type
КУРБЕЛ	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
СПИЦИ	Sapim
ГУМИ	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
ЕКСТРИ	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

ГЕОМЕТРИЯ

РАМКА	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76,2°	76,6°	77,0°	76,2°	76,6°	77,0°	77,3°	77,6°	78,0°	77,3°	77,6°	78,0°
Top Tube Length (mm)	552	552	550	567	566	565	581	580	579	603	602	600
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7°	65,1°	65,5°	64,6°	65,1°	65,5°	64,8°	65,1°	65,5°	64,8°	65,1°	65,5°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131	127,9	124,8	131,6	127,8	124,8	130,6	127,7	124,8	130,5	127,7	124,8
Wheelbase (mm)	1166	1166	1164	1183	1180	1179	1208	1207	1207	1232	1231	1231
Chain Stay Length (mm)	443	442	440	443	442	440	443	442	440	443	442	440
Bottom Bracket Drop (mm)	25	20	15	24	20	15	35	30	25	35	30	25
Stack (mm)	629	627	624	628	627	624	628	625	622	637	634	633
Обсер (mm)	398	402	406	413	417	421	439	442	447	459	462	466
Stand Over Height (mm)	613	613	613	674	674	674	712	712	712	750	750	750
Ширина на Кормило (mm)	760			760			760			780		
Дължина на Лапа (mm)	40			50			50			50		
Дължина на Курбел (mm)	165			170			170			170		
Размер на Каплите	F 29 R 27.5			F 29 R 27.5			29"			29"		

All specifications listed are subject to change without notice.