

INTRIGUE LT ADVANCED 1



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
ΧΡΩΜΑΤΑ	Raw Carbon
ΣΚΕΛΕΤΟΣ	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
ΠΙΠΟΥΝΙ	Fox 36 Performance Elite, 160mm, Grip 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
ΑΝΑΡΤΗΣΗ	Fox Float X Performance Elite 185x55, custom tuned for Liv
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
ΛΑΙΜΟΣ ΣΤΕΛΛΑΣ	TranzX travel-adjustable dropper, remote XS: 125mm travel/ 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
ΣΤΕΛΛΑ	Liv Sylvia
ΠΕΝΤΑΛ	platform
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM AXS, 1x12
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	SRAM GX T-Type
ΦΡΕΝΑ	Shimano XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano XT BL-M8100
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM GX T-Type, 10x52
ΑΛΥΣΙΔΑ	SRAM GX T-Type
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
ΚΕΝΤΡΑ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
ΑΚΤΙΝΕΣ	Sapim
ΕΛΑΣΤΙΚΑ	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	230			250			280			310		
Seat Tube Angle	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°			77,3° 77,6° 78,0°			77,3° 77,6° 78,0°		
Top Tube Length (mm)	552 552 550			567 566 565			581 580 579			603 602 601		
Head Tube Length (mm)	95			95			100			110		
Head Tube Angle	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°			64,8° 65,1° 65,5°			64,8° 65,1° 65,5°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	131 127,9 124,8			131,6 127,8 124,8			130,6 127,7 124,8			130,5 127,7 124,8		
Wheelbase (mm)	1166 1166 1164			1183 1180 1179			1208 1207 1207			1232 1231 1231		
Chain Stay Length (mm)	443 442 440			443 442 440			443 442 440			443 442 440		
Bottom Bracket Drop (mm)	25 20 15			24 20 15			35 30 25			35 30 25		
Stack (mm)	629 627 624			628 627 624			628 625 622			637 634 631		
Reach (mm)	398 402 406			413 417 421			439 442 447			459 462 466		
Stand Over Height (mm)	613 613 613			674 674 674			712 712 712			750 750 750		
Handlebar Width (mm)	760			760			760			780		
Stem Length (mm)	40			50			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	F 29 R 27.5			F 29 R 27.5			29"			29"		

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση