



SPECS

FRAME	
SIZES	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLORS	Raw Carbon
FRAME	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
FORK	Fox 36 Performance Elite, 160mm, Grip 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
SHOCK	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
STEM	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEATPOST	TranzX travel-adjustable dropper, remote XS: 125mm travel/ 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SADDLE	Liv Sylvia
PEDALS	platform
DRIVETRAIN	
SHIFTERS	SRAM AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX T-Type
BRAKES	Shimano XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano XT BL-M8100
CASSETTE	SRAM GX T-Type, 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

Price: ₹ 7,500.00

GEOMETRY

FRAME	XS	S	M
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	370	390	420
Seat Post Insertion Depth (mm)	230	250	280
Seat Tube Angle	76.2° 76.6° 77.0°	76.2° 76.6° 77.0°	77.3° 77.6° 78.0°
Top Tube Length (mm)	552 552 550	567 566 565	581 580 579
Head Tube Length (mm)	95	95	100
Head Tube Angle	64.7° 65.1° 65.5°	64.6° 65.1° 65.5°	64.8° 65.1° 65.5°
Fork Rake (mm)	44	44	44
Trail (mm)	131 127.9 124.8	131.6 127.8 124.8	130.6 127.7 124.8
Wheelbase (mm)	1166 1166 1164	1183 1180 1179	1208 1207 1207
Chain Stay Length (mm)	443 442 440	443 442 440	443 442 440
Bottom Bracket Drop (mm)	25 20 15	24 20 15	35 30 25
Stack (mm)	629 627 624	628 627 624	628 625 622
Reach (mm)	398 402 406	413 417 421	439 442 447
Stand Over Height (mm)	613 613 613	674 674 674	712 712 712
Handlebar Width (mm)	760	760	760
Stem Length (mm)	40	50	50
Crank Length (mm)	165	170	170
Wheel Size	F 29 R 27.5	F 29 R 27.5	29"