

INTRIGUE LT ADVANCED 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
COLORES	Raw Carbon
CUADRO	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip - Maestro 3, integrated down tube storage
TIJERA	Fox 36 Performance Elite, 160mm, Grip 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
AMORTIGUADOR	Fox Float X Performance Elite 185x55, custom tuned for Liv
COMPONENTES	
MANUBRIO	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
POTENCIA	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
POSTE DE ASIENTO	TranzX travel-adjustable dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
ASIENTO	Liv Sylvia
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX T-Type
FRENOS	Shimano XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
PALANCAS DE FRENOS	Shimano XT BL-M8100
CASSETTE	SRAM GX T-Type, 10x52
CADENA	SRAM GX T-Type
MULTIPLICACIÓN	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYOS	Sapim
NEUMÁTICOS	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

Precio: \$159,990.00

GEOMETRÍA

CUADRO	XS		S		M	
	LOW	MID HIGH	LOW	MID HIGH	LOW	MID HIGH
Longitud de la Base del Poste de Asiento (mm)	370		390		420	
Seat Post Insertion Depth (mm)	230		250		280	
Ángulo de la Base del Poste de Asiento	76.2° 76.6° 77.0°		76.2° 76.6° 77.0°		77.3° 77.6° 78.0°	
Longitud del Tubo Superior (mm)	552 552 550		567 566 565		581 580 579	
Longitud del Telescopio (mm)	95		95		100	
Ángulo del Telescopio	64.7° 65.1° 65.5°		64.6° 65.1° 65.5°		64.8° 65.1° 65.5°	
Rake (mm)	44		44		44	
Trail (mm)	131 127.9 124.8		131.6 127.8 124.8		130.6 127.7 124.8	
Distancia entre Ejes (mm)	1166 1166 1164		1183 1180 1179		1208 1207 1207	
Longitud de Vaina Inferior (mm)	443 442 440		443 442 440		443 442 440	
Caída del Eje de Centro (mm)	25 20 15		24 20 15		35 30 25	
Stack (mm)	629 627 624		628 627 624		628 625 622	
Reach (mm)	398 402 406		413 417 421		439 442 447	
Altura del Tubo Superior al Suelo (mm)	613 613 613		674 674 674		712 712 712	
Ancho del Manubrio (mm)	760		760		760	
Longitud de la Potencia (mm)	40		50		50	
Longitud de la Biela (mm)	165		170		170	
Tamaño de las Ruedas	F 29 R 27.5		F 29 R 27.5		29"	

Todas las especificaciones están sujetas a cambios sin previo aviso.