

INTRIGUE LT ADVANCED 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S: MX only, M, L: 29" F&R out of the box, MX compatible
FARBY	Raw Carbon
RÁM	Advanced-grade composite front and rear triangles, 150mm Maestro Suspension, flip chip – Maestro 3, integrated down tube storage
VIDLICA	Fox 36 Performance Elite, 160mm, Grip 2 damper, Boost 15x110 Kabolt, tapered, 44mm offset
TLMIČ	Fox Float X Performance Elite 185x55, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact SLR TR35, composite, 20mm rise, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIPY	Liv Tactal Pro Single Lock-On XS/S: 120mm, M/L: 130mm
PREDSTAVEC	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SEDLOVKA	TranzX travel-adjustable dropper, remote XS: 125mm travel / 30.9 x 390mm S: 120-150mm travel / 30.9 x 390mm M: 150mm travel / 30.9 x 440mm L: 150mm travel / 30.9 x 440mm
SEDADLO	Liv Sylvia
PEDÁLE	platform
POHON	
RADENIE	SRAM AXS, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM GX T-Type
BRZDY	Shimano XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano XT BL-M8100
KAZETA	SRAM GX T-Type, 10x52
REŤAZ	SRAM GX T-Type
KLUKY	SRAM GX T-Type, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant TRX 2 Carbon WheelSystem, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NÁBOJE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
ŠPICE	Sapim
PNEUMATIKY	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
DOPLNKY	MRP 1259-HD2CS-0001 chain guide, 3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 32t

Cena: 7 499 €

GEOMETRIA

RÁM	XS			S			M		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	370			390			420		
Hĺbka vloženia sedlovky (mm)	230			250			280		
Uhol sedlovej trubky	76,2° 76,6° 77,0°			76,2° 76,6° 77,0°			77,3° 77,6° 78,0°		
Dĺžka hornej rámovej trubky (mm)	552 552 550			567 566 565			581 580 579		
Dĺžka hlavovej trubky (mm)	95			95			100		
Uhol hlavovej trubky	64,7° 65,1° 65,5°			64,6° 65,1° 65,5°			64,8° 65,1° 65,5°		
Offset vidlice (mm)	44			44			44		
Trail (mm)	131 127,9 124,8			131,6 127,8 124,8			130,6 127,7 124,8		
Rázvor (mm)	1166 1166 1164			1183 1180 1179			1208 1207 1207		
Dĺžka zadnej stavby (mm)	443 442 440			443 442 440			443 442 440		
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	25 20 15			24 20 15			35 30 25		
Stack - výška riadenia (mm)	629 627 624			628 627 624			628 625 622		
Reach (mm)	398 402 406			413 417 421			439 442 447		
Výška rámu od zeme (mm)	613 613 613			674 674 674			712 712 712		
Šírka riaditok (mm)	760			760			760		
Dĺžka predstavca (mm)	40			50			50		
Dĺžka klúku (mm)	165			170			170		
Rozmer kolies	F 29 R 27.5			F 29 R 27.5			29"		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.